112 8554 TW22-OB1W WATER WELL RECORD Form WWC-5 Division of Water Resources; App. No.	
1 LOCATION OF WATER WELL: Fraction Section Number Township Number Range N SE 1/4 NW 1/4 NW 1/4 27 T 12 S R 22	lumber (E) W
Distance and direction from nearest town or city street address of well if located within city? Approximately 1/8 mile north and 1/4 mile east of DeSoto Global Positioning Systems (decimal degrees, min. of Latitude: 38.983047 Longitude: -94.960191	\sim
2 WATER WELL OWNER: City of Olathe RR#, St. Address, Box # : P.O. Box 768 Elevation: Unknown Datum: NAD83	
City State 7ID Code	
3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL 60 ft.	
Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) WELL'S STATIC WATER LEVEL Not checked ft. below land surface measured on mo/day/yr Pump test data: Well water was Not checked ft. after hours pumping Est. Yield Unknown gpm: Well water was ft. after hours pumping WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well WELL WATER TO BE USED AS: 5 Public water supply 9 Dewatering 12 Other (Specify	gpm gpm
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Observat Was a chemical/bacteriological sample submitted to Department? Yes No V If yes, mo/	
Sample was submitted Water well disinfected? Yes No	dayryis
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Casing diameter 2 in. to 48 ft., Diameter in. to ft., Diameter in. to Casing height above land surface 24 in., weight .70 lbs./ft. Wall thickness or gauge No154 TYPE OF SCREEN OR PERFORATION MATERIAL:	
Steel 3 Stainless Steel 5 Fiberglass (7) PVC 9 ABS 11 Other (Specify)	
2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)	
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (Specify) SCREEN-PERFORATED INTERVALS: From 48 ft. to 58 ft., From ft. to ft.	
From ft. to ft., From ft. to GRAVEL PACK INTERVALS: From 40 ft. to 60 ft., From ft. to	c. 1
From ft. to ft., From ft. to 6 GROUT MATERIAL: Neat Cement 2 Cement grout 3 Bentonite 4 Other Bentonite Holeplug	ft.
Grout Intervals: From ft. to ft., From	
2 Sewel lines 9 Sewage lagoon 11 Tues storage 14 None kno	own
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil well/gas well 14 How many feet?	
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS	
0 5 Topsoil	
5 16 Clay, dark gray, hard 16 31 Sand and gravel, medium to fine, loose	
31 57 Sand and gravel, medicin to fine, loose 31 57 Sand and gravel, coarse to fine, with streaks,	
large rock	
57 60 Limestone, gray, hard	
	plugged
under my jurisdiction and was completed on (mo/day/year) 11-14-06 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on mo/day/year) 11-14-06	
Under the business name of Clarke Well & Equipment, Inc. by (signature)	
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each <u>constructed</u> well.	