

1 LOCATION OF WATER WELL: County: Johnson		Fraction SW 1/4 SE 1/4 SE 1/4	Section Number 11	Township Number T 12 S	Range Number R 24 (E)W
Distance and direction from nearest town or city street address of well if located within city? 10608 West 63rd Street, Shawnee, Kansas					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Amoco Oil Company 8700 Indian Creek Parkway, Suite 180 Overland Park, KS 66210 Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: <div style="text-align: center;"> </div>		4 DEPTH OF COMPLETED WELL: 13.2 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 4.4 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 4.28 ft. below land surface measured on mo/day/yr 11/20/89 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 6 in. to 13.2 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 <u>Monitoring well</u> Was a chemical/bacteriological sample submitted to Department? Yes.....No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 <u>PVC</u> 4 ABS Blank casing diameter 2 in. to 3.2 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface -0.55 in., weight lbs./ft. Wall thickness or gauge No. SCH. 40		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded X TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 <u>Mill slot</u> 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 3.2 ft. to 10.0 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 2.0 ft. to 13.2 ft., From ft. to ft. From ft. to ft., From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 2 <u>Cement grout</u> 3 Bentonite 4 Other Grout Intervals: From 0.0 ft. to 1.0 ft., From 1.0 ft. to 2.0 ft., From ft. to ft.		What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? Southwest How many feet? 100			
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0.0 0.4 Asphalt					
0.4 0.8 Gravel					
0.8 4.3 Silty Clay, Mottled Gray-Brown Becoming Dark Brown					
4.3 9.3 Silty Clay, Dark Gray-Brown Becoming Mottled Gray-Brown					
9.3 13.2 Silty Clay, Mottled Gray-Brown					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/17/89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 12/8/89 under the business name of Terracon Consultants by (signature) <i>[Signature]</i>					