

1 LOCATION OF WATER WELL: County: Johnson		Fraction SE 1/4 SE 1/4 NW 1/4	Section Number 23	Township Number T 12 S	Range Number R 24
Distance and direction from nearest town or city street address of well if located within city? 75th & Nieman Rd. shawnee Mission, Ks.					
2 WATER WELL OWNER: Amoco Oil co. RR#, St. Address, Box #: 8700 Indian Creek Pkwy, Suite 100 City, State, ZIP Code: Overland Park, KS. 66210 Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: <div style="text-align: center;"> </div>		4 DEPTH OF COMPLETED WELL: 13.0 ft. ELEVATION: Depth(s) Groundwater Encountered 1. Dry ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 4.76 ft. below land surface measured on mo/day/yr 1-18-90 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 6 in. to 13.0 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 in. to 3.0 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface 46Ft weight lbs./ft. Wall thickness or gauge No. SCH 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 3.0 ft. to 12.0 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 2.0 ft. to 13.0 ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement X Cement grout X Bentonite 4 Other Grout Intervals: From 0 ft. to 1.0 ft. From 1.0 ft. to 2.0 ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? Northwest How many feet? 40'					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5	Silty clay loam (fill)			Seams, organics becoming yellowish brown with stiff laminated silt seams possibly weathered shale
0.5	11.0	Very silty clay, light gray mottled red, with trace yellow, moist, friable to soft, block, wet gray silt seaming throughout some hematite nodules and root casting			
11.0	13.0	Fat clay, reddish brown, mottled reddish gray, moist, stiff, trace rounded coarse sand, with gray silt			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-20-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 1-31-90 under the business name of Terracon Consultants by (signature) <i>Douglas S. Semley</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					