


1 LOCATION OF WATER WELL: County: Johnson Fraction: NW 1/4 NW 1/4 SE 1/4 Section Number: 23 Township Number: T 12 S Range Number: R 24 E

Distance and direction from nearest town or city street address of well if located within city?
7720 State Line Road, Prairie Village, Ks.

2 WATER WELL OWNER: Shell Oil Products, U.S.
 RR#, St. Address, Box #: 308 Wilcox # 101 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Castle Rock, Colo 80104 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:


4 DEPTH OF COMPLETED WELL: 15'6" ft. ELEVATION:
 Depth(s) Groundwater Encountered: 1.10' ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL: 7.05 ft. below land surface measured on mo/day/yr: 8-4-04
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No (No)

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded X

Blank casing diameter: 2.375 in. to 5' ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface: Flush Mt. in., weight lbs./ft. Wall thickness or gauge No: Sub 4 D

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify)
 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) ft.

SCREEN-PERFORATED INTERVALS: From 15' ft. to 5' ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 15'6" ft. to 4' ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other: Concrete
 Grout Intervals: From 4' to 2' ft., From 2' to Surface ft., From ft. to ft.

What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage

Direction from well? North West to West North West How many feet? 120'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3.0	dk Brn to Black silty clay w/ roots.			
		fur			
3.0	6.50	grayish Brn to Brn clay w/ iron oxide staining, fur to 4.00			
6.50	11.0	grayish Brn clay, wet			
11.0	15.6	Red Brn clay, hard to wet, no odor			
					F.M. OK'd by D. Taylor
					RECEIVED
					AUG 31 2004
					BUREAU OF WATER

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-30-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 732 This Water Well Record was completed on (mo/day/yr) 8-23-04 under the business name of GBEN Sewell & Supply by (signature) James Becker