

--

Check: ☒ White Copy, ☐ Blue Copy, ☐ Pink Copy

					LOG OF BORING NO: <b>MW-06R</b>		SHEET NUMBER 1 OF 1	
PROJECT NAME: <b>Amoco #2225</b>					DRILLING/PROBING CONTRACTOR: <b>Razek Environmental</b>		<b>Water Level Data</b> Date      Depth	
PROJECT LOCATION: <b>15421 W 87th St Pkwy</b>					DRILLING METHOD / BORE DIAMETER: <b>Hollow Stem Auger 8.25"/4.25"</b>			
PROJECT NUMBER: <b>17102308</b>					SAMPLING METHOD: <b>MacroCore</b>		<b>Survey Data</b> Ground Surface: Top Of Casing: Ground Water:	
GEOLOGIST: <b>Meredith Watson</b>					TOTAL DEPTH (feet): <b>6.5</b>			
DRILLER: <b>Tony Poultier</b>					START DATE: <b>10/04/10</b>			
					COMPLETION DATE: <b>10/04/10</b>			
SAMPLE DEPTH AND TIME	PID (PPMV)	RECOVERY (FEET)	DEPTH (FEET)	WELL CONSTRUCTION	GEOLOGIC DESCRIPTION (NAME, color, particle size, characteristics)	NOTES:		
1020	2.0	3/5	1	<div style="display: flex; align-items: center;"> <div style="width: 10px; height: 10px; background: repeating-linear-gradient(45deg, transparent, transparent 2px, black 2px, black 4px); margin-right: 5px;"></div> <div style="writing-mode: vertical-rl; transform: rotate(180deg); font-size: 8px;">CONCRETE</div> </div> <div style="display: flex; align-items: center;"> <div style="width: 10px; height: 10px; background: repeating-linear-gradient(-45deg, transparent, transparent 2px, black 2px, black 4px); margin-right: 5px;"></div> <div style="writing-mode: vertical-rl; transform: rotate(180deg); font-size: 8px;">BENTONITE CHIP SEAL</div> </div> <div style="display: flex; align-items: center;"> <div style="width: 10px; height: 10px; background: repeating-linear-gradient(-45deg, transparent, transparent 2px, black 2px, black 4px); margin-right: 5px;"></div> <div style="writing-mode: vertical-rl; transform: rotate(180deg); font-size: 8px;">2" Sch. 40 PVC RISER</div> </div> <div style="display: flex; align-items: center;"> <div style="width: 10px; height: 10px; background: repeating-linear-gradient(45deg, transparent, transparent 2px, black 2px, black 4px); margin-right: 5px;"></div> <div style="writing-mode: vertical-rl; transform: rotate(180deg); font-size: 8px;">10-20 SAND FILTER PACK</div> </div> <div style="display: flex; align-items: center;"> <div style="width: 10px; height: 10px; background: repeating-linear-gradient(-45deg, transparent, transparent 2px, black 2px, black 4px); margin-right: 5px;"></div> <div style="writing-mode: vertical-rl; transform: rotate(180deg); font-size: 8px;">2" Sch. 40 PVC SCREEN</div> </div>	Asphalt Surface			
			2		gravel			
			3		CH: dk gy, CLAY, damp, plastic, stiff			
			4					
			5		CL: orange, silty CLAY, moist, TR plastic, medium stiff			
1025	0.7	1/1	6		CL: orange, silty CLAY, damp, non-plastic, medium stiff limestone nodules	Collected sample MW06R-A 2-3 ft interval at 1025, no odor		
1030	NR	NR			Sampler Refusal at 6 ft, continue with augers			
1100			7		Refusal at 6.5 ft			
			8					
			9					
			10					
			11					
			12					
			13					
			14					
			15					
			16					
			17					
			18					
			19					
			20					
			21					
			22					
			23					
			24					
			25					

**LEGEND:**

SS - Split Spoon  
PID - Photoionization Detector  
NR - No Recovery

- Concrete

- Flush Mount Vault

- Grout

- Bentonite Chip Seal

- Filter Pack

- Well Screen

ST - Shelby Tube  
HSA - Hollow Stem Augers  
PPMV - Parts Per Million by Volume