

WATER WELL RECORD Form WWC-5

Division of Water Resources App. No.

MW-2


Original Record Correction Change in Well Use

Well ID

1 LOCATION OF WATER WELL: County: Johnson Fraction 1/4 SE 1/4 SE 1/4 NE 1/4 Section Number 10 Township Number T 12 S Range Number R 24 E

2 WELL OWNER: Last Name: First: Street or Rural Address where well is located: Dry Cleaners Plus 12101 Johnson Drive, Shawnee, KS 66216

3 LOCATE WELL WITH "X" IN SECTION BOX: N



4 DEPTH OF COMPLETED WELL: 21.5 ft. Depth(s) Groundwater Encountered: 1) 12 ft. 2) N/A ft. 3) N/A ft. or 4) Dry Well WELL'S STATIC WATER LEVEL: 12.00 ft.

5 Latitude: 39.0223021 Longitude: -94.7260944 Horizontal Datum: WGS 84 Source for Latitude/Longitude: GPS

6 Elevation: 1011.81 ft. Source: Land Survey

7 WELL WATER TO BE USED AS: 1. Domestic 2. Irrigation 3. Feedlot 4. Industrial 5. Public Water Supply 6. Dewatering 7. Aquifer Recharge 8. Monitoring 9. Environmental Remediation 10. Oil Field Water Supply 11. Test Hole 12. Geothermal 13. Other

Was a chemical/bacteriological sample submitted to KDHE? No Water well disinfected? No

8 TYPE OF CASING USED: PVC CASING JOINTS: Threaded Casing diameter 2 in. to 11.5 ft. Diameter N/A in. to N/A ft. Casing height above land surface 0 in. Weight N/A lbs./ft. Wall thickness or gauge No. Sch. 40

TYPE OF SCREEN OR PERFORATION MATERIAL: PVC SCREEN OR PERFORATION OPENINGS ARE: Mill Slot

SCREEN-PERFORATED INTERVALS: From 11.5 ft. to 21.5 ft. GRAVEL PACK INTERVALS: From 9.5 ft. to 21.5 ft.

9 GROUT MATERIAL: Concrete 0 to 2 Grout Intervals: From 2 ft. to 9.5 ft.

Nearest source of possible contamination: Former Dry Cleaner Site Direction from well? Northeast Distance from well? <75-feet

Table with columns: 10 FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHO. LOG (cont.) or PLUGGING INTERVALS. Content: Detailed boring logs attached.

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year) 5/11/2022



# BORING LOG

LOCATION ID: MW- 2

PROJECT: C4-046-73711 / 204.02.002

DATE: 5/ 11 /22

SITE ADDRESS:

Dry Cleaning Plus, 12101 Johnson Drive, Shawnee, KS

CLIENT:

KDHE

DRILLING CONTRACTOR:

Razek Drilling

DRILLING/SAMPLING METHOD:

HSA

LOGGED BY:

Kimberly Fitzpatrick, PE, RG

DRILLER:

Tony Poulter

DRILL RIG:

GeoProbe

BORING DIAMETER:

8"

Piezometer/Well: YES

BORING DEPTH:

21.5'

ELEV. (feet amsl)	DEPTH (feet bgs)	DESCRIPTION OF MATERIALS	GRAPHIC	PID READING (ppm)	RECOVERY %	SAMPLE	REMARKS
	0	Approximately 6 inches asphalt					1400 began drilling PID collected via headspace in ziploc bag
	1	dark brown, firm, medium plasticity, ~10% fine sand, ~5% up to 20 mm subrounded gravel, lean clay (CL)		0.3			Well Completion Details: 10 foot well screen 21.5'-11.5' 6 bags sand 21.5'-9.5' 2.5 bags bentonite pellets 5 gallons of water flushmount surface casing
	2						
	3						
	4						
	5			0.8			
	6						
	7						
	8						
	9			1.5			
	10						

COMMENTS: continued on Sheet 2

SHEET

SHEETS

amsl = above mean sea level bgs = below ground surface

1

OF

3



# BORING LOG

LOCATION ID: MW- 2

PROJECT: C4-046-73711 / 204.02.002

DATE: 5/ 11 /22

SITE ADDRESS:

Dry Cleaning Plus, 12101 Johnson Drive, Shawnee, KS

CLIENT:

KDHE

DRILLING CONTRACTOR:

Razek Drilling

DRILLING/SAMPLING METHOD:

HSA

LOGGED BY:

Kimberly Fitzpatrick, PE, RG

DRILLER:

Tony Poulter

DRILL RIG:

GeoProbe

BORING DIAMETER: 8"

Piezometer/Well: YES

BORING DEPTH: 21.5'

ELEV. (feet amsl)	DEPTH (feet bgs)	DESCRIPTION OF MATERIALS	GRAPHIC	PID READING (ppm)	RECOVERY %	SAMPLE	REMARKS
	11	Same as above, dark brown, firm, medium plasticity, ~10% fine sand, ~5% up to 20 mm subrounded gravel, lean clay (CL)		1.0			
	12						
	13						
	14				0.7		
	15						
	16	Moist					
	17			1.3			Refusal at 17'
	18						
	19						
	20						

COMMENTS: continued on Sheet 3 (if applicable)

SHEET

SHEETS

amsl = above mean sea level bgs = below ground surface

2

OF

3



# BORING LOG

LOCATION ID: MW-2

PROJECT: C4-046-73711 / 204.02.002

DATE: 5/ 11 /22

SITE ADDRESS:

Dry Cleaning Plus, 12101 Johnson Drive, Shawnee, KS

CLIENT:

KDHE

DRILLING CONTRACTOR:

Razek Drilling

DRILLING/SAMPLING METHOD:

HSA

LOGGED BY:

Kimberly Fitzpatrick, PE, RG

DRILLER:

Tony Poulter

DRILL RIG:

GeoProbe

BORING DIAMETER:

8"

Piezometer/Well: YES

BORING DEPTH:

21.5'

ELEV. (feet amsl)	DEPTH (feet bgs)	DESCRIPTION OF MATERIALS	GRAPHIC	PID READING (ppm)	RECOVERY %	SAMPLE	REMARKS
		dark brown, firm, medium plasticity, ~10% fine sand, lean clay (CL)		0.8			
	21	Refusal at 21.5'					
	22						
	23						
	24						
	25						
	26						
	27						
	28						
	29						
	30						

COMMENTS:

SHEET

SHEETS

amsl = above mean sea level    bgs = below ground surface

3

OF


3



# Dry Cleaners Plus

Approximate Monitoring Well Locations

## Legend

 Feature 1

