

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: JOHNSON		NW 1/4 NW 1/4 SE 1/4	30	T 12 S	R 24 E
Distance and direction from nearest town or city street address of well if located within city? 700 N. ROGERS ROAD					
2 WATER WELL OWNER: BDAT ENVIRONMENTAL, INC.			Board of Agriculture, Division of Water Resources		
RR#, St. Address, Box #: 1862 CRAIGSHIRE DR.			Application Number:		
City, State, ZIP Code: ST. LOUIS, MO 63146					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 18 ft. ELEVATION:			
		Depth(s) Groundwater Encountered: 1. 14.6 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL: ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was NA ft. after hours pumping gpm			
		Est. Yield: gpm Well water was NA ft. after hours pumping gpm			
		Bore Hole Diameter: 8 in. to 18 in. and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only ☒ Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No ☒			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)		5 Wrought iron	
☒ PVC		4 ABS		6 Asbestos-Cement	
				7 Fiberglass	
Blank casing diameter: 2 in. to 8 ft. Dia				8 Concrete tile	
Casing height above land surface: 24 in. weight				9 Other (specify below)	
TYPE OF SCREEN OR PERFORATION MATERIAL:				CASING JOINTS: Glued Clamped	
1 Steel		3 Stainless steel		5 Wrought iron	
2 Brass		4 Galvanized steel		6 Asbestos-Cement	
				7 Fiberglass	
				8 Concrete tile	
SCREEN OR PERFORATION OPENINGS ARE:				9 Other (specify below)	
1 Continuous slot		☒ Mill slot		5 Wrought iron	
2 Louvered shutter		4 Key punched		6 Asbestos-Cement	
				7 Fiberglass	
				8 Concrete tile	
SCREEN-PERFORATED INTERVALS:				9 Other (specify below)	
From: 8 ft. to 18 ft.				5 Wrought iron	
				6 Asbestos-Cement	
				7 Fiberglass	
				8 Concrete tile	
GRAVEL PACK INTERVALS:				9 Other (specify below)	
From: 6 ft. to 18 ft.				5 Wrought iron	
				6 Asbestos-Cement	
				7 Fiberglass	
				8 Concrete tile	
6 GROUT MATERIAL:					
1 Neat cement		☒ Cement grout		☒ Bentonite	
Grout Intervals: From: 0 ft. to 4 ft.		From: 4 ft. to 6 ft.		4 Other	
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines		10 Livestock pens	
2 Sewer lines		5 Cess pool		☒ Fuel storage	
3 Watertight sewer lines		☒ Seepage pit		12 Fertilizer storage	
				13 Insecticide storage	
				14 Abandoned water well	
				15 Oil well/Gas well	
				16 Other (specify below)	
Direction from well? S				How many feet? 30	
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	FILL			
5	10	CLAY			
10	18	SILTY CLAY			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/7/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 571 This Water Well Record was completed on (mo/day/yr) 9/20/94 under the business name of BDAT ENVIRONMENTAL, INC. by (signature)					