

02958015

MW-13

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: JOHNSON	SW 1/4 SW 1/4 NE 1/4	30	T 12 S	R 25 W

Distance and direction from nearest town or city street address of well if located within city?

8205 SANTA FE OVERLAND PARK, KS

2 WATER WELL OWNER:	MW-13
RR#, St. Address, Box #:	Board of Agriculture, Division of Water Resources
City, State, ZIP Code:	Application Number:
TOWN & COUNTRY	
P.O. BOX 17807	
WICHITA, KS 67217	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 15.0 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL . ft. below land surface measured on mo/day/yr Pump test data: Well water was . ft. after . hours pumping . gpm Est. Yield . gpm: Well water was . ft. after . hours pumping . gpm Bore Hole Diameter: 8.0 in. to . ft., and . in. to . ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes . No . ☒ If yes, mo/day/yr sample was submitted . Water Well Disinfected? Yes . No . ☒

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued . Clamped .
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded .
Blank casing diameter 2.0 in. to 4.7 ft. Dia . in. to . ft. Dia . in. to . ft.			Threaded . ☒
Casing height above land surface . 6 in., weight . lbs./ft. Wall thickness or gauge No. SCHED 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot 0.010"	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched 4.7	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 4.7 ft. to 14.7 ft.		
	From . ft. to . ft.		
GRAVEL PACK INTERVALS:	From 2.7 ft. to 15.0 ft.		
	From . ft. to . ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:	From 0.0 ft. to 0.7 ft.	From 0.7 ft. to 2.7 ft.	From . ft. to . ft.	From . ft. to . ft.
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	14 Abandoned water well
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	15 Oil well/Gas well
				16 Other (specify below)
Direction from well?	SOUTH WEST			
				How many feet? 90

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	0.5	TOPSOIL			
0.5	10.0	BRN SILTY CLAY			
10.0	11.5	WEATHERED GRAY LS			
11.5	14.5	OLIVE GREEN SHALE			
14.5	15.0	WEATHERED GRAY LS			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-10-95 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 3-18-96
under the business name of TERRACON CONSULTANTS by (signature) [Signature]