

1 LOCATION OF WATER WELL: County: Johnson		Fraction NE 1/4 SW 1/4 SE 1/4		Section Number 3		Township Number T 12 S		Range Number R 25 EW		
Distance and direction from nearest town or city street address of well if located within city? 2814 Shawnee Mission Parkway, Fairway, KS										
2 WATER WELL OWNER: Amoco Oil Company RR#, St. Address, Box #: 8700 Indian Creek Parkway City, State, ZIP Code: Overland Park, KS 66210 Board of Agriculture, Division of Water Resources Application Number:										
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL: 13 Ft ft. ELEVATION:							
			Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.							
			WELL'S STATIC WATER LEVEL 7.42 ft. below land surface measured on mo/day/yr 2/19/92							
			Pump test data: Well water was ft. after hours pumping gpm							
			Est. Yield gpm: Well water was ft. after hours pumping gpm							
Bore Hole Diameter 6 in. to 23 ft. and in. to ft.			WELL WATER TO BE USED AS:							
1 Domestic			3 Feedlot		6 Oil field water supply		9 Dewatering		12 Other (Specify below)	
2 Irrigation			4 Industrial		7 Lawn and garden only		10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted										
Water Well Disinfected? Yes No X										
5 TYPE OF BLANK CASING USED:										
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped										
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded										
7 Fiberglass Threaded Flush										
Blank casing diameter 2 in. to 3 ft. Dia in. to ft. Dia in. to ft.										
Casing height above land surface 0 in. weight lbs./ft. Wall thickness or gauge No. Sch-40										
TYPE OF SCREEN OR PERFORATION MATERIAL:										
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement										
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)										
12 None used (open hole)										
SCREEN OR PERFORATION OPENINGS ARE:										
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)										
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes										
7 Torch cut 10 Other (specify)										
SCREEN-PERFORATED INTERVALS: From 3 ft. to 13 ft. From ft. to ft.										
From ft. to ft. From ft. to ft.										
GRAVEL PACK INTERVALS: From 2 ft. to 14 ft. From ft. to ft.										
From ft. to ft. From ft. to ft.										
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other										
Grout Intervals: From 0 ft. to 1 ft. From 1 ft. to 2 ft. From 14 ft. to 15 ft.										
What is the nearest source of possible contamination:										
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well										
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well										
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)										
13 Insecticide storage										
Direction from well? North How many feet? 8										
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS										
0 8.5 Grey silty clay, stiff										
8.5 13 Orange clay, stiff, plastic										
13 23 Orange silty clay, stiff										
End of boring										
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/28/90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. This Water Well Record was completed on (mo/day/yr) 3/5/92 under the business name of Geraghty & Miller, Inc. by (signature) J. Lloyd										
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.										