


1 LOCATION OF WATER WELL: County: <u>Johnson</u>		Fraction MW 1/4 SW 1/4 SW 1/4		Section Number <u>15</u>	Township Number T <u>12</u> S	Range Number R <u>25</u> <u>EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>6901 Mission Road, Prairie Village</u>						
2 WATER WELL OWNER: <u>AMOCO Oil Company</u>		Board of Agriculture, Division of Water Resources				
RR#, St. Address, Box #: <u>8700 Indian Creek Parkway</u>		Application Number:				
City, State, ZIP Code: <u>Overland Park, KS 66210</u>						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: <u>14.5</u> ft. ELEVATION: Depth(s) Groundwater Encountered <u>1</u> <u>10</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>6.92</u> ft. below land surface measured on mo/day/yr <u>2/20/92</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <u>6</u> in. to <u>14.8</u> ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only <u>10 Monitoring well</u> Was a chemical/bacteriological sample submitted to Department? Yes.....No <u>X</u> If yes, mo/day/yr sample was sub- mitted Water Well Disinfected? Yes No <u>X</u>				
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped <u>2 PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded. Flush..... Blank casing diameter <u>2</u> in. to <u>4.5</u> ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface <u>0</u> in., weight lbs./ft. Wall thickness or gauge No. <u>Schedule 40</u> TYPE OF SCREEN OR PERFORATION MATERIAL: <u>7 PVC</u> 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot <u>3 Mill slot</u> 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From <u>4.5</u> ft. to <u>14.5</u> ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From <u>2.5</u> ft. to <u>14.8</u> ft., From ft. to ft. From ft. to ft., From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement <u>2 Cement grout</u> <u>3 Bentonite</u> 4 Other Grout Intervals: From <u>0</u> ft. to <u>1.3</u> ft., From <u>1.3</u> ft. to <u>2.5</u> ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy <u>11 Fuel storage</u> 14 Abandoned water well <u>2 Sewer lines</u> 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below) Direction from well? <u>South</u> How many feet? <u>110</u>						
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
0	0.6 Ft	Asphalt overlying concrete pavement				
0.6	4.5 Ft	Dark olive grey, moist clayey silt				
4.5	12.5	Dark olive grey with green tint, moist clayey silt				
12.5	15.8	Olive green and orange, wet silty clay with rock fragments				
13.8	14.8	Light grey, hard shale				
		End of Boring.				

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2/20/92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. This Water Well Record was completed on (mo/day/yr) 3/3/92 under the business name of Geraghty & Miller, Inc. by (signature) S. Lloyd