

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number																																																							
County: Johnson		NW ¼ SW ¼ SW ¼		15		T 12 S		R 25 EW																																																							
Distance and direction from nearest town or city street address of well if located within city?																																																															
6901 Mission Road, Prairie Village																																																															
2 WATER WELL OWNER:		AMOCO Oil Company																																																													
RR#, St. Address, Box # :		8700 Indian Creek Parkway																																																													
City, State, ZIP Code :		Overland Park, KS 66210																																																													
		Board of Agriculture, Division of Water Resources																																																													
		Application Number:																																																													
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 13.8 ft. ELEVATION:																																																													
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.																																																													
		WELL'S STATIC WATER LEVEL 6.74 ft. below land surface measured on mo/day/yr 2/19/92																																																													
		Pump test data: Well water was ft. after hours pumping gpm																																																													
		Est. Yield gpm: Well water was ft. after hours pumping gpm																																																													
		Bore Hole Diameter 6 in. to 15 ft., and in. to ft.																																																													
		WELL WATER TO BE USED AS:																																																													
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well																																																													
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted																																																													
		Water Well Disinfected? Yes No X																																																													
5 TYPE OF BLANK CASING USED:																																																															
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Flush 7 Fiberglass Threaded																																																															
Blank casing diameter in. to ft., Dia in. to ft., Dia in. to ft.																																																															
Casing height above land surface -3 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40																																																															
TYPE OF SCREEN OR PERFORATION MATERIAL:																																																															
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)																																																															
SCREEN OR PERFORATION OPENINGS ARE:																																																															
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)																																																															
SCREEN-PERFORATED INTERVALS: From 3.8 ft. to 13.8 ft., From ft. to ft.																																																															
GRAVEL PACK INTERVALS: From 2.0 ft. to 15.0 ft., From ft. to ft.																																																															
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other																																																															
Grout Intervals: From 0 ft. to 1 ft., From 1 ft. to 2 ft., From ft. to ft.																																																															
What is the nearest source of possible contamination:																																																															
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage																																																															
Direction from well? Northwest How many feet? 130																																																															
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>0.6 Ft</td> <td>Asphalt pavement with base of sand and gravel</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.6</td> <td>3</td> <td>Moderate olive green, grey, dry, brittle silty clay</td> <td></td> <td></td> <td></td> </tr> <tr> <td>3</td> <td>5</td> <td>Moderate dark brown, damp silt with some clay</td> <td></td> <td></td> <td></td> </tr> <tr> <td>5</td> <td>6.5</td> <td>Moderate grey and orange, damp silty clay</td> <td></td> <td></td> <td></td> </tr> <tr> <td>6.5</td> <td>13</td> <td>Dark grey to black, damp to wet, clayey silt</td> <td></td> <td></td> <td></td> </tr> <tr> <td>13</td> <td>14</td> <td>Grey and orange weathered shale</td> <td></td> <td></td> <td></td> </tr> <tr> <td>14</td> <td>15</td> <td>Moderate grey, hard, brittle shale</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>End of boring.</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>										FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	0.6 Ft	Asphalt pavement with base of sand and gravel				0.6	3	Moderate olive green, grey, dry, brittle silty clay				3	5	Moderate dark brown, damp silt with some clay				5	6.5	Moderate grey and orange, damp silty clay				6.5	13	Dark grey to black, damp to wet, clayey silt				13	14	Grey and orange weathered shale				14	15	Moderate grey, hard, brittle shale						End of boring.			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																										
0	0.6 Ft	Asphalt pavement with base of sand and gravel																																																													
0.6	3	Moderate olive green, grey, dry, brittle silty clay																																																													
3	5	Moderate dark brown, damp silt with some clay																																																													
5	6.5	Moderate grey and orange, damp silty clay																																																													
6.5	13	Dark grey to black, damp to wet, clayey silt																																																													
13	14	Grey and orange weathered shale																																																													
14	15	Moderate grey, hard, brittle shale																																																													
		End of boring.																																																													
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2/6/92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. This Water Well Record was completed on (mo/day/yr) 3/3/92 under the business name of Geraghty & Miller, Inc. by (signature) S. Lloyd																																																															