

1 LOCATION OF WATER WELL: County: <u>Johnson</u>	Fraction <u>NW 1/4 SW 1/4 NE 1/4</u>	Section Number <u>30</u>	Township Number <u>T 12 S</u>	Range Number <u>R 25 E/W</u>
---	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

8130 Santa Fe Drive, Overland Park

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code	<u>Texaco USA</u> <u>8620 West 110th Suite 200</u> <u>Overland Park</u>	Board of Agriculture, Division of Water Resources Application Number: <u>MW-9</u>
---	---	---

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL <u>14</u> ft. ELEVATION:
--	--

Depth(s) Groundwater Encountered 1 4 ft. 2 4 ft. 3 4 ft.

WELL'S STATIC WATER LEVEL top of casing below land surface measured on mo/day/yr 3-15-90

Pump test data: Well water was 7.25 gpm. Well water was 14 ft. after 14 hours pumping 7.25 gpm.

Est. Yield 7.25 gpm. Well water was 14 ft. after 14 hours pumping 7.25 gpm.

Bore Hole Diameter 7.25 in. to 14 ft. and 14 in. to 14 ft.

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering	11 Injection well
2 Irrigation	4 Industrial	7 Lawn and garden only	<u>10 Monitoring well</u>	12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>No</u> <u>X</u> Clamped
------------------------------	----------------	-----------------	---

1 Steel

2 PVC

3 RMP (SR)

4 ABS

Blank casing diameter 4 in. to 4 ft. Dia 4 in. to 4 ft. Dia 4 in. to 4 ft.

Casing height above land surface 0 in. weight 0 lbs./ft. Wall thickness or gauge No. 5/16

6 Asbestos-Cement

7 Fiberglass

9 Other (specify below)

Welded No X Threaded

TYPE OF SCREEN OR PERFORATION MATERIAL:	10 Asbestos-cement
---	--------------------

1 Steel

2 Brass

3 Stainless steel

4 Galvanized steel

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot

2 Louvered shutter

3 Mill slot

4 Key punched

5 Fiberglass

6 Concrete tile

8 RMP (SR)

9 ABS

11 Other (specify)

12 None used (open hole)

5 Gauzed wrapped

6 Wire wrapped

7 Torch cut

8 Saw cut

9 Drilled holes

10 Other (specify)

11 None (open hole)

SCREEN-PERFORATED INTERVALS:	From <u>4</u> ft. to <u>14</u> ft.	From <u>4</u> ft. to <u>14</u> ft.	From <u>4</u> ft. to <u>14</u> ft.
GRAVEL PACK INTERVALS:	From <u>2</u> ft. to <u>14</u> ft.	From <u>2</u> ft. to <u>14</u> ft.	From <u>2</u> ft. to <u>14</u> ft.

6 GROUT MATERIAL:	1 Neat cement	<u>2 Cement grout</u>	<u>3 Bentonite</u>	4 Other
-------------------	---------------	-----------------------	--------------------	---------

Grout Intervals: From 0 ft. to 1 ft. From 1 ft. to 2 ft. From 2 ft. to 10 ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	<u>16 Other (specify below)</u>

Direction from well? East

How many feet? 10

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>13.5</u>	<u>brown, fine sandy clay</u>			
<u>13.5</u>	<u>14</u>	<u>Limestone</u>			
<u>Casing height and grout variance granted</u>					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1) constructed</u> (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>3-10-90</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>517</u> This Water Well Record was completed on (mo/day/yr) <u>3/29/90</u> under the business name of <u>Groundwater Tech. Inc.</u> by (signature) <u>[Signature]</u>
