	WATER WELL RECORD Form WWC-5 KSA 82a-1212 ID No. MW-3A	
1 LOCATION OF WATER WELL:	Fraction Section Number Township Number Range Num	nber
County: Johnson		B W
	n or city street address of well if located within city?	
4700 Lamar Avenue, Mission, Ka		
WATER WELL OWNER: Quik Trip RR#, St. Address, Box # : 901 N. M		
Au Au	Nilaharra 74446	sources
3 LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX:	Oklahoma 74116 Application Number:	
AN "X" IN SECTION BOX:	DEPTH OF COMPLETED WELL 6.0 ft. ELEVATION:	
	Depth(s) Groundwater Encountered 1 114 11. 2 11. 3	ft. 💃
↑ 	WELL'S STATIC WATER LEVEL Dry ft. below land surface measured on mo/day/yr 03/28/	<u>05 </u>
NW NE	Pump test data: Well water was ft. afterhours pumping	gpm ç
	Est. Yield NA gpm: Well water was ft. after hours pumping	gpm j
E E E	Bore Hole Diameter 8.5 in. to 6.0 ft. and in. to	ft.
	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well	helow)
	2 Irrigation 4 Industrial 7 Lawn and garden (domestic) (10) Monitoring well	DC1011)
 	Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample	le was
	submitted Water Well Disinfected? Yes No	
5 TYPE OF BLANK CASING USED:	5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamp	
1 Steel 3 RMP (SI	SR) 6 Asbestos-Cement 9 Other (specify below) Welded	
2PVC 4 ABS	7 Fiberglass Threaded X	
Blank casing diameter 2.375	in. to 3.0 ft., Dia in. to ft., Dia in. to	ft.
	ush Mount in., weight Ibs./ft. Wall thickness or gauge No. Schedule	
ITVDE OE CODEEN OD DEDEODATION	IMATERIAL: 7 DVC 40 Ashestes sement	
1 Steel 3 Stainles	ss steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	
2 Brass 4 Galvaniz	ized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
SCREEN OR PERFORATION OPENING 1 Continuous slot (3) M	• • • • • • • • • • • • • • • • • • • •	hole)
2 Louvered shutter 4 K	· ·	
SCREEN-PERFORATED INTERVALS:		ft
	From ft. to ft. From ft. to	
GRAVEL PACK INTERVALS:		
	From ft. to ft. From ft. to	I .
6 GROUT MATERIAL: 1 Neat ce	ement 2Cement grout 3Bentonite 4 Other	
Grout Intervals From 0.0 ft	t. to 1.0 ft. From 1.0 ft. to 2.0 ft. From ft. to	ft.
What is the nearest source of possible co		
1 Septic tank	4 Lateral lines 7 Pit privy (11) Fuel storage 15 Oil well/ Gas well	
2 Sewer lines	5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below	v)
3 Watertight sewer lines 6	6 Seepage pit 9 Feedyard 13 Insecticide storage	
Direction from well?	Southwest How many feet? 170	
FROM TO CODE	LITHOLOGIC LOG	
	wn very silty clay, very firm, moist	
	l-brown very silty clay, limestone stringers, very firm, moist	
	nt olive green very silty clay, limestone stringers, very firm, moist, trace odor	-
	TO THE TOTAL PARTY OF THE PARTY	
	Flush-mount well completion approved by Don Taylor, KDHE, BOW.	
		/
	'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction are	
completed on (mo/day/yr)	03/24/05 and this record is true to the best of my knowledge and belief. Ka	ansas 14/05
Water Well Contractor's License No.		7,03
under the business name of INSTRUCTIONS: Please fill in blanks a	and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 100	00 S W
	66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.	