	WELL REC	CORD Form WW				on of Water ces App. No.		Well ID	MW6
	ginal Record						r Township Num		
1 LO		VATER WELL:	Fraction NW 1/4 SW 1/4	SW ¼ NW		Section Numbe 29	T 12		Number 5 X E W
	LL OWNER: L	ast Name:	First:		- '		ll is located (if unkn		
Business: Mac's 66, Inc. from nearest town or intersection): If at owner's address, check here:									
1	ress: 8139 Metca	alf Ave.							
Addi		ad Dark State: VS	ZIP: 66204						
3 LOC	Overlan	4 DEPTH OF COM	MPLETED WELL:	14.56 ft	5	Latitude:	38.9803	31 (de	cimal degrees)
	TH "X" IN	Depth(s) Groundwater E	ncountered: 1)	ft		Longitude	94.6672	24 (de	cimal degrees)
SEC	CTION BOX:	2)ft 3)	ft, or 4)1	Dry Well			Datum: WGS 8		83 NAD 27
	N	WELL'S STATIC WAT				Latitude/Longitude:		,	
	1	X below land surface		2-		nit make/model:)	
мм	V NE -	above land surface Pump test data: Well	y-yr) ft		(WAAS enabled? Yes No) X Land Survey Topographic Map				
x 1		1 1	irs pumping	gpm		=	Mapper		
w x		Wa	ter well was	ft					
L sw	, SE -		irs pumping	gpm	6		1069.09 ft	Ground Le	· · · · · · · · · · · · · · · · · · ·
l I .	,	Estimated Yield:	gpm			===	Land Survey	_	Topographic Map
		Bore Hole Diameter:	7.25 in to in to	ft, and			Other		
	1 mile		III 10	11					
7 WELL WATER TO BE USED AS:									
1 Domesti		5 Public Water Sup			_	_	/ater Supply: lease		
==	sehold	6 Dewatering: how	-		11 7	Test Hole: well		70	
==	n & Garden	7 Aquifer Recharge			12.0	Cased Geothermal: Hov	Uncased	Geotechnic	ai
. =	estock gation	8 X Monitoring: well 9 Environmental Remed				a) Closed Loop		Vertica	
3 Feed	•	Air Sparge	Soil Vapor Extract	ior		b) Open Loop		scharge	
==	ıstrial	Recovery	Injection		Γ	Other (spec			•
Was a chemical/bacteriological sample submitted to KDHE? Yes X No If yes, date sample was submitted:									
Was a chemical/bacteriological sample submitted to KDHE? Yes X No If yes, date sample was submitted: Water well disinfected? Yes X No									
8 TYPE OF CASING USED: Steel X PVC Other CASING JOINTS: Glued Clampled Welded X Threaded									
Casing diameter 2 in to 5.06 ft, Diameter in to ft, Diameter in to ft,									
Casing height above land surface -0.35 in. Weight lbs./ft. Well thickness or gauge No									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
Steel Stainless Steel Fiberglass X PVC Other (Specify)									
Brass Galvanized Steel Concrete tile None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:									
Continuous Slot X Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify) Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole)									
									ft,
GRA	AVEL PACK IN	TERVALS: From 4	ft. to 15 ft,	From	 ft. t	to f	t, From	ft. to	ft,
GRAVEL PACK INTERVALS: From 4 ft. to 15 ft, From ft. to ft, From ft. to ft, 9 GROUT MATERIAL: Neat cement Cement grout X Bentonite X Other Concrete: 0-0.5'									
Grout intervals: From 0.5 ft. to 4 ft, From ft. to ft, From ft. to ft,									
	***************************************	contamination:		.,					
	ic Tank	Lateral Lines	Pit Privy		ivesto	ck Pens	Insecticide	Storage	
Sewe	er Lines	Cess Pool	Sewage Lagoon		uel Sto	•		Water Well	
	ertight Sewer Line	Seepage Pit	Feedyard	F	ertilize	er Storage	Oil Well / (Gas Well	
	er (Specity)		Distance Con-				£		
Direction fro		,	Distance from w		,	TO 1	ft		
10 FROM		LITHOLOG	IC LOG	FROM	1	TO	LITHO. LOG (con	t.) or PLUGGIN	IG INTERVALS
0.7		Topsoil Silty clay			-				
	+								
	+			Notes: K	DHE	ID: Mac's 66	Service; U4-046-1	2100	
							,		
									
		R LANDOWNER'S CERTIFIC			_	· ——	reconstructed, or		under my
jurisdiction License N		[d was completed on (m			knowledge an	d deliel. Kansas W	ater Well Con	tractor's
under the business name of Larsen & Associates, Inc. Signature									
	Mail 1 white c	opy along with a fee of \$5.00 for eac	h constructed well to: Kan	sas Department of	Health	and Environme			
1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your feetings. Telephong 783-290 5524									
Visit us	s at http://www.kdhe	eks.gov/waterwell/index.html	KSA 82a	-1212				Revised	7/10/2015