		RECORD		WWC-5		vision of Water	· ·			
		Correction		ge in Well Use		ources App. No		Well ID		
1 LOCATION OF WATER WELL:			Fraction		ction Number			ge Number		
	: Johnson			SE 1/4 NE 1/4 NE 1/4		10 T 12 S R 25 ■ E □ W				
2 WELL OWNER: Last Name: Lockton First: Mark Street or Rural Address where well is located (if unknown, distance ar										
Business: Address: 2321 W. 59th Street direction from nearest town or intersection): If at owner's address, check he									check here:	
Address:	2321 VV.	Saut Suee	L	Į.						
City:	Mission	Hills	State: KS	ZIP: 66208						
3 LOCAT		1	TH OF COL	APLETED WELL:						
WITH "	X" IN	Donth(s)	Groundwater	Encountered: 1)9	0 ft. Longitude: -94.612587 (decimal degrees)				(decimal degrees)	
SECTION BOX:			3) ft., or 4)			ntal Datum: WGS 8				
N WELL'S STATIC W			STATIC WA	TER LEVEL:	ft.		for Latitude/Longitude		65 L NAD 21	
			below land surface, measured on (mo-day-yr				S (unit make/model:)	
			above land surface, measured on (mo-day-yr)				(,			
			Pump test data: Well water was			Land Survey Topographic Map				
W X E after				vater was fi		■ Online Mapper: WGS84				
1 077 1 05 1 1				s numning gnm						
				anm		6 Elevation:ft. Ground Level TOC				
S Bore Hole Diame			e Diameter:	5.5/8 in to 334	. ft. and	Source:				
	1 mile in. to ft. Other									
7 WELL WATER TO BE USED AS:										
1. Domestic:										
, —	☐ Household 6. ☐ Dewatering: ho									
			echarge: well ID	^						
	2. Irrigation 9. Environmental Remedia									
_ 0						•				
4. Industr	rial		☐ Recovery	☐ Injection		13. 🔲 Oth	ner (specify):			
Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted:										
Water well disinfected? ☐ Yes ■ No										
8 TYPE OF CASING USED: ☐ Steel ☐ PVC ■ Other HD POLY CASING IOINTS: ☐ Glued ☐ Clamped ■ Welded ☐ Threaded										
Casing diameter										
Casing height above land surface										
TYPE OF SCREEN OR PERFORATION MATERIAL:										
☐ Steel ☐ Stainless Steel ☐ Fiberglass ☐ PVC ☐ Other (Specify)										
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:										
☐ Continuous Slot ☐ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)										
☐ Contanuous Stot ☐ Willin Stot ☐ Gauze Wrapped ☐ Toleff Cut ☐ Diffied Holes ☐ Guer (Speeny)										
SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft., From ft., From ft. to ft.										
GRAVEL PACK INTERVALS: From ft. to ft., From ft., From ft., From ft.										
9 GROUT MATERIAL: ■ Neat cement □ Cement grout ■ Bentonite □ Other Grout Intervals: From 334 ft. to 304 B ft., From 304 ft. to 204 C ft., From 204 ft. to 0 B ft.										
Nearest source of possible contamination:										
☐ Septic			Lateral Line			Livestock Per		icide Storage		
☐ Sewer Lines ☐ Cess Pool ☐ Sewage Lagoon ☐ Fuel Storage ☐ Abandoned Water Well ☐ Watertight Sewer Lines ☐ Seepage Pit ☐ Feedyard ☐ Fertilizer Storage ☐ Oil Well/Gas Well										
Other (Specify)										
Direction from well?										
10 FROM	TO		LITHOLO		FROM		LITHO. LOG (cont.) o		G INTERVALS	
0	18		118-145 lin				3-334' Bores Plugg	ed		
18	26		145-150 sh				334-304 Bentonite			
26	31		150-171 lin		334		304-204 Cement			
31	38	lime	171-174 st			2	204-0 Bentonite			
38	63		174-190 lin							
63	71	lime	190-296 sh							
71	87		296-302 oi		Notes:					
87	91		302-334 st	nale	-					
91 118 shale										
under my jurisdiction and was completed on (mo-day-year) .1/10/2018 and this record is true to the best of my knowledge and belief.										
Kansas Wa	ter Well Co	ontractor's L	icense No.	561 This Wa	ter Well Re	cord was con	pleted on (mo-day-y	(r) 1/15/2	Ž018	
under the b	usiness nar	neof Evaņ	s.Energy.D	evelopment, inc	S	ignatu re	100 G C			
Mail	I white copy a	long with a fee	of \$5.00 for ea	ch constructed well to: Kan	sas Departmen	t of He alth a nd I	Environment, Bureau of V	Vater, GWTS S	Section,	
1			-	66612-1367. Mail one to			e for your records. Telep			
Visit us at http	Visit us at http://www.kdheks.gov/waterwell/index.html KSA 82a-1212 Revised 7/10/2015									