


1 LOCATION OF WATER WELL: Fraction NW ¼ SW ¼ SW ¼ Section Number 15 Township Number T 12 S Range Number R 25 (EW)
 County: Johnson
 Distance and direction from nearest town or city street address of well if located within city?
 6901 Mission Road, Prairie Village, Kansas

2 WATER WELL OWNER: AMOCO Oil Company
 RR#, St. Address, Box #: 8702 Indian Creek Parkway
 City, State, ZIP Code: Building 3, Suite 190, Overland Park, Kansas 6610
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 DEPTH OF COMPLETED WELL: 14 ft. ELEVATION: 911.18
 Depth(s) Groundwater Encountered 1. 6.94 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL: 6.94 ft. below land surface measured on m/day/yr 6/26/74
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter: 6 1/4 in. to ft. and in. to ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below)
 Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, m/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SRP) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 Blank casing diameter 2 in. to ft. Dia. in. to ft. Dia. in. to ft.
 Casing height above land surface: -0.3 in. weight lb./ft. Wall thickness or gauge No.
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SRP) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)
 7 Torch cut
 SCREEN-PERFORATED INTERVALS: From 3.5 ft. to 14.0 ft. From ft. to ft.
 GRAVEL PACK INTERVALS: From 1.5 ft. to 14.5 ft. From ft. to ft.
 From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout intervals: From 0.5 ft. to 1.5 ft. From ft. to ft. From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 PR privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage Unknown
 Section from well?
 FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS
 0.5 5.0 Grey Brown silty clay - fill 0.5 1.5 Bentonite
 5.0 11.0 Water at 4.0 with drillings 1.5 14.5 Gravel Pack
 5.0 11.0 Silty clay (CL)
 11.0 12.0 Grey shale

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (m/day/year) 5/24/94 and this record is true to the best of my knowledge and belief, Kansas
 Water Well Contractor's License No. 534 This Water Well Record was completed on (m/day/yr) 6/15/94
 under the business name of Professional Service Ind. by (signature) L. C. Rasmussen

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRINT FULLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 813-294-5545. Send one to WATER WELL OWNER and retain one for your records.

OCT 26 1994