

NAME OF WATER WELL:

Fraction

Section Number

Township Number

Range Number

Johnson

NW 1/4 SW 1/4 SW 1/4

15

T 12 S

R 25 E

Location and direction from nearest town or city street address of well if located within city?

6901 Mission Road, Prairie Village, Kansas

WATER WELL OWNER: Amoco Oil Company

R/R, St. Address, Box #: 8700 INDIAN CREEK PKWY, Bldg. 3, Suite 190

City, State, ZIP Code: Overland Park, Kansas 66210

Board of Agriculture, Division of Water Resource

Application Number:

LOCATE WELL'S LOCATION WITHIN AN "X" IN SECTION BOX:

DEPTH OF COMPLETED WELL: 35.5 ft. ELEVATION: 912.58

Depth(s) Groundwater Encountered: 1. DRY ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL: DRY ft. below land surface measured on m/day/yr

Pump test date: Well water was ft. after hours pumping gpm

Est. Yield: Well water was ft. after hours pumping gpm

Bore Hole Diameter: 6 in. to ft. and in. to ft.

WELL WATER TO BE USED AS:

1 Domestic

3 Feedlot

5 Public water supply

8 Air conditioning

11 Infection well

2 Irrigation

4 Industrial

6 Oil field water supply

9 Dewatering

12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, m/day/yr sample was submitted

Water Well Disinfected? Yes No

TYPE OF BLANK CASING USED:

1 Steel

3 RMP (SR)

5 Wrought iron

8 Concrete tile

CASING JOINTS: Glued Clamped

2 PVC

4 ABS

6 Asbestos-Cement

9 Other (Specify below)

Welded

Blank casing diameter: 2 in. to ft. Dia. in. to ft. Dia. in. to ft. Dia.

Casing height above land surface: 0.3 in. weight lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel

3 Stainless steel

5 Fiberglass

7 PVC

10 Asbestos-cement

2 Brass

4 Galvanized steel

6 Concrete tile

8 RMP (SR)

11 Other (Specify)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot

3 Wire slot

5 Gauzed wrapped

8 Saw cut

11 None (open hole)

2 Louvered shutter

4 Key punched

6 Wire wrapped

9 Drilled holes

7 Torch cut

10 Other (Specify)

SCREEN-PERFORATED INTERVALS:

From: 20.5 ft. to 35.5 ft. From: ft. to ft. From: ft. to ft. From: ft. to ft.

GRAVEL PACK INTERVALS:

From: 4.0 ft. to 40.0 ft. From: ft. to ft. From: ft. to ft. From: ft. to ft.

GROUT MATERIAL:

1 Neat cement

2 Cement grout

3 Bentonite

4 Other

Grout intervals: From: ft. to ft. From: ft. to ft. From: ft. to ft. From: ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank

4 Lateral lines

7 Pit privy

10 Livestock pens

14 Abandoned water well

2 Sewer lines

5 Cess pool

8 Sewage lagoon

11 Fuel storage

15 Oil well/Gas well

3 Waterflood power lines

6 Seepage pit

9 Feedyard

12 Fertilizer storage

16 Other (Specify below)

13 Insecticide storage

Unknown

Section from well?

FROM TO

LITHOLOGIC LOG

FROM TO

PLUGGING INTERVALS

0.5 4

Olive Clay (CH)

0 40

Bentonite

4 8

Interbedded limestone and shale

4 40

Gravel Pack

8 9

Light Grey Shale

9 11

Tan Limestone

11 21

Light grey shale

21 24

Tan Limestone

24 29

Burgundy Shale

29 35

Limestone

OCT 26 1994

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (m/day/yr) 5/23/94 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 534

This Water Well Record was completed on (m/day/yr) 10/19/94

Under the business name of Professional Service Inc.

by (signature) L. O. Johnson

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRINT FULLY and fill clearly. Please fill in circles, underline or circle the correct answers. Send two true copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-6843. Send one to WATER WELL OWNER and retain one for your records.