


1 LOCATION OF WATER WELL: County: Dickinson Fraction: SE 1/4 SR 1/4 SE 1/4 Section Number: 7 Township Number: T 12 S Range Number: R 3 E
 Distance and direction from nearest town or city street address of well if located within city? From Abilene Co 7 miles North on 15 Highway To 18 then 60 3 1/2 miles East on 18 + 60 1 mile South on Dirt Road
 2 WATER WELL OWNER: Mrs. Herb Gravis
 RR#, St. Address, Box #: P.O. Box 452 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Chapman, Kansas 67431 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 200' ft. ELEVATION:
 Depth(s) Groundwater Encountered: 1. 168' ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL: 150' ft. below land surface measured on mo/day/yr
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield: 40 gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter: 8" in. to 200' ft., and in. to ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes..... No.....; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)
 2 PVC 4 ABS 7 Fiberglass
 Blank casing diameter: 5" in. to 180' ft. Dia. in. to ft. Dia. in. to ft.
 Casing height above land surface: 2' in., weight sch 40 lbs./ft. Wall thickness or gauge No.
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 3/1000s 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 180' ft. to 200' ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 25' ft. to 200' ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout intervals: From 0 ft. to 25' ft., From ft. to ENVIRPLUG From ft. to ft.
 What is the nearest source of possible contamination: None Close
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	28	Brown Clay	124	129	Shale
28	33	Yellow Clay	129	141	Rock
33	35	Greenish Shale	141	168	Shale
35	44	Brown Shale	168	177	Rock (Water)
44	47	Rock	177	184	Shale
47	53	Grey Shale	184	187	Rock
53	57	Rock	187	195	Shale
57	65	Grey Shale	195	200	Rock
65	70	Rock			
70	88	Shale			
88	89	Rock			
89	95	Shale			
95	119	Rock			
119	120	Rock			
120	124	Rock			

I was Drilling Blindly
 Couldn't Tell What Colors
 I was in From 70' Down

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/5/88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 451 This Water Well Record was completed on (mo/day/yr) 7/26/88 under the business name of Haldeman Well Drilling by (signature) Craig Hal CND/PE

OFFICE USE ONLY
T
R
EW
SEC.
1/4
1/4
1/4