


1 LOCATION OF WATER WELL: Fraction SW 1/4 NW 1/4 NE 1/4 Section Number 18 Township Number T 12 S Range Number R 3 E/W
 County Dickinson
 Distance and direction from nearest town or city street address of well if located within city?
3 1/2 miles East of Abilene, Ks on 1st to Jeep Rd go 5 miles North to 2800 Ave go

2 WATER WELL OWNER: Dusty Kuntz 1 mile East to Key Rd & 3/4 North
 RR#, St. Address, Box #: 2331 Flay Rd Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Abilene, Kansas 67410 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL 200 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1 1.85 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 153 ft. below land surface measured on mo/day/yr 10 / 18 / 04
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 10.4 gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No *; If yes, mo/day/yrs sample was submitted
 Water Well Disinfected? Yes * No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued * Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 200 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 1.5 in., weight 200 lbs./ft. Wall thickness or gauge No. 2.50
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 180 ft. to 200 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 24 ft. to 200 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

RECEIVED
 NOV 15 2004
 BUREAU OF WATER

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Asbestos water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? SOUTHWEST WILL BE APPROX How many feet? 365

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	DARK CLAY	113	114	LITE GRAY SHALE
5	17	BROWN & TAN CLAY	114	130	LITE COLOR LIMESTONE
17	42	LITE COLOR CLAY	130	137	LITE COLOR SHALE
42	49	RED CLAY & SHALE	137	144	GRAY SHALE
49	73	LITE COLOR SHALE & MIXED LITE GRAY	146	148	HARD LITE COLOR LIMESTONE
73	74	LITE COLOR LIMESTONE	148	162	LITE COLOR SHALE
74	75	CAVEPY	162	173	GRAY SHALE
75	76	LITE COLOR SHALE	173	180	RED SHALE
76	79	HARD LIMESTONE	180	185	RED & GRAY MIXED SHALE
79	89	GRAY SHALE	185	196	GRAY SHALE
89	90	LITE COLOR LIMESTONE	196	198	HARD GRAY LIMESTONE
90	94	LITE COLOR SHALE	198	200	DARK GRAY SHALE
94	97	LITE GRAY SHALE			GRAY HARD LIMESTONE
97	113	RED SHALE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10 / 18 / 04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 397 This Water Well Record was completed on (mo/day/yr) 10 / 31 / 04 under the business name of CENTRAL KANSAS DRILLING by (signature) Harold B. Martin