

1 LOCATION OF WATER WELL: Fraction NE 1/4 SW 1/4 SW 1/4 Section Number 33 Township Number T 12 S Range Number R 3 E 1/4 *
 County: Dickinson

Distance and direction from nearest town or city street address of well if located within city?
5 1/2 miles East of Abilene, Ks on I-70 to Exit 281 go North to 2502 Mink Rd

2 WATER WELL OWNER: Four Seasons R.V. Park
 RR#, St. Address, Box # : 2502 Mink Rd Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Abilene, Kansas 67410 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
---	NW	---	NE
W			E
---	SW	---	SE
S			

4 DEPTH OF COMPLETED WELL 88 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 5.7 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 5.6 ft. below land surface measured on mo/day/yr 4 / 22 / 0.5
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 15+ gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No *
 Water Well Disinfected? Yes * No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued * Clamped
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
2 PVC 4 ABS 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 8.8 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 1.6 in., weight 20.0 lbs./ft. Wall thickness or gauge No. 250
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-Cement
 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify)
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 5.6 ft. to 8.8 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 2.4 ft. to 8.8 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 2.4 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? SOUTH WILLBE APPROX How many feet? 400

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	BROWN CLAY			
5	9	LITE COLOR CLAY			
9	17	LITE COLOR SHALE			
17	20	HARD LITE COLOR LIMESTONE			
20	23	LITE COLOR SHALE & CLAY			
23	27	GRAY CLAY & SHALE			
27	36	LITE COLOR & LITE GRAY CLAY & SHALE			
36	52	MAROON & GRAY MIXED SHALE			
52	57	GRAY SHALE & CLAY			
57	62	LITE COLOR SHALE			
62	70	HARD LIMESTONE LITE COLOR			
70	71	LITE COLOR SHALE			
71	77	HARD LIMESTONE			
77	88	LITE COLOR SHALE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4 / 22 / 05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 397 This Water Well Record was completed on (mo/day/yr) 4 / 25 / 05 under the business name of CENTRAL KANSAS DRILLING by (signature) Arnold R. Martin