WATER WELL RECORD	Form WWC	:-5	Division	n of Water	r Resources; App. No.	
1 LOCATION OF WATER WELL: County: DICKINSIA	Fraction NEA NEA	VW.	Section No	umber		Range Number R / M/W
Distance and direction from nearest town or cit located within city?	y street address of w	ell if G			Systems (decimal deg	
located within city?	60 9 MI		L atitude:			
East on I 10 to 43 they Go 2 Mill North 1 Fast			Longitude:			
RR#, St. Address, Box # 2628 Na/L Rd			Elevation:			
City, State, ZIP Code	10 / 11/1/A		Datum:	lastian N	Mathad.	
3 LOCATE WELL'S 4 DEPTH OF COMP	TETED WELL	140	Data Coll	ft	vietnod:	
LOCATION		-				
WITH AN "X" IN Depth(s) Groundwater	Encountered (1).	90	ft.	(2)	ft. (3).	ft.
SECTION BOX: WELL'S STATIC WA	TER LEVEL		below land	d surface	measured on mo/day	/yr
N Pump test data Est. Yield. 3.0gpm	: Well water was	• • • • • • • • • • • • • • • • • • • •	tt. atter		hours pumping.	gpm
WELL WATER TO BE	E USED AS: 5 Pub	lic water s	upply	8 Air c	conditioning 11 In	ection well
W Domestic 3 Feed	dlot 6 Oil field	d water sup	ply	9 Dew	ratering 12 Or	ther (Specify below)
2 Irrigation 4 Indi	ustrial 7 Domest	tic (lawn &	garden)	10 Mon	itoring well	
SW SE Was a shamisal/hastari	ماده المعادة المعادة	mittad ta D	\	49 V	N.	IC
Was a chemical/bacteri Sample was submitted.	ological sample sub	mitted to L Water	epartment well disin	t? Yes	Ved No	If yes, mo/day/yrs
S Sample was saomitted.		Water	wen disin	nected	110	••••
5 TYPE OF CASING USED: 5 Wrought I	ron 8 Con	crete tile		CASINO	JOINTS Glued.	Clamped
1 Steel 3 RMP (SR) 6 Asbestos-	Cement 9 Othe	r (specify	below)		Welded	
FVC 4 ABS 7 Fiberglass					Threaded	1
Blank casing diameter in. to ./2.0	ft., Diameter	ir	n. to	ft.,	Diameter	in. toft.
Casing height above land surface	in., weight.	7 4.0	lbs./π.	wall thic	ckness or guage No.	
1 Steel 3 Stainless Steel 5 Fibers		9 Al	BS		11 Other (Specify)	
2 Brass 4 Galvanized Steal 6 Concr	rete tile 8 RM (SI	R) 10 A	sbestos-C	ement	12 None used (oper	
SCREEN OR PERFORATION OPENINGS ARE		1	0 D -111	111	1137	1.
1 Continuous slot Mill slot 5 Gu 2 Louvered shutter 4 Key punched 6 W					11 None (open h	
SCREEN-PERFORATED INTERVALS: From	/.2.0 ft. to	140	ft., l	From	ft. to	ft.
SCREEN-PERFORATED INTERVALS: From From	ft. to	,	ft., l	From	ft. to	ft.
GRAVEL PACK INTERVALS: From	£ ft. to	140	ft.,	From	ft. to .	ft.
From	11. to		π., I	From	ft. to	π.
6 GROUT MATERIAL: 1 Neat cement 2 0						
Grout Intervals: From ft. to 2.			t. to	ft	., From	ft. toft.
What is the nearest source of possible contaminating Septic tank 4 Lateral lines		10 Livesto	ck nans	13 Inc	ecticide Storage	16 Other (specify
		11 Fuel sto			andoned water well	below)
3 Watertight sewer lines 6 Seepage pit		12 Fertilize			well/gas well	
Direction from well?		How many	1			
FROM TO LITHOLOGIC	LOG	FROM	TO	18-	PLUGGING INT	ERVALS
1 9 Participal		10	1211	1)/04	M 2 MI JA	
9 12 tingstand		120	139	LIM	15/00	
12 50 Ten Shelf		154	140	Grig	SHILL	
50 58 Limistore				1		
88. 64 Cerry		-				
64 66 BNOTON					.	
66 90 Stown 3 1911						
TO MANITOR						
7 CONTRACTOR'S OR LANDOWNER'S CE	RTIFICATION: T	his water v	well was () constr	ucted, (2) reconstruct	ted, or (3) plugged
under my jurisdiction and was completed on (mo/o	lay/year) . 8 . 12.5.	. 2006 d	this record	l is true to	o the best of my know	wledge and belief
I Vancon Water Wall Contractor's Linear Ma	/ This Water	· Wall Dag	andaa aa	mnlatad	((1 ()	50 / '1 '2 /7 VIV'
Kansas Water Well Contractor's License No					on (mo/day/year)	EZATET
under the business name of	VILL ON W	by	(signature	re) /	nes //	Eagil
	SE PRESS FIRMLY and the Bureau of Water, Geolo	by PRINT clearly by Section, 1	(signature y. Please fill 1000 SW Jac	e) I in blanks, ekson St., S	, underline of the the c uite 420, Topeka, Kansas	orrect answers. Send top 66612-1367. Telephone