


1 LOCATION OF WATER WELL: County: Dickenson Fraction Ne 1/4 Me 1/4 Section Number 30 Township Number T 12 S Range Number R 4 E

Distance and direction from nearest town or city Street address of well if located within city?
1 N Chapman

2 WATER WELL OWNER: John Harrison
RR#, St. Address, Box #: RR 2 Box 103
City, State, ZIP Code: Chapman, KS 67431
Board of Agriculture, Division of Water Resources
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 86.75 ft. ELEVATION:
Depth(s) Groundwater Encountered 1. 69 ft. 2. 7-13-89 ft. 3. 85 ft.
WELL'S STATIC WATER LEVEL 69 ft. below land surface measured on mo/day/yr
Pump test data: Well water was 20 gpm Well water was 7 1/2 ft. after 85 hours pumping 20 gpm
Est. Yield 20 gpm Well water was 7 1/2 ft. after 85 hours pumping 20 gpm
Bore Hole Diameter 2 1/2 in. to 30 ft. and 7 1/2 in. to 85 ft.
WELL WATER TO BE USED AS:
5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
7 Fiberglass Threaded

Blank casing diameter 5 in. to 55 ft. Dia. in. to 12 in. weight Class 160 lbs./ft. Wall thickness or gauge No. 214

TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 55 ft. to 86 ft., From 25 ft. to 86 ft.
GRAVEL PACK INTERVALS: From 25 ft. to 86 ft., From 25 ft. to 86 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Hole plug
Grout Intervals: From 5 ft. to 25 ft., From 25 ft. to 85 ft.

What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage
Direction from well? E How many feet? 85

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	fine sand			
2	40	yellow clay			
40	75	lime			
75	76	Water			
76	86	Blue Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-13-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 180 This Water Well Record was completed on (mo/day/year) 7-13-89 under the business name of Backhus Drilling by (signature) Paul J. Backhus