

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Dickinson</u>	<u>SE 1/4 NE 1/4 SE 1/4</u>	<u>29</u>	<u>T 12 S</u>	<u>R 4 E/W *</u>

Distance and direction from nearest town or city street address of well if located within city?
1 mile East of Chapman, Ks on old Hwy 40 & 3/8 mile North & 1/2 mile West

2 WATER WELL OWNER: Sean Fink
 RR#, St. Address, Box # : 2643 Sage Rd Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Chapman, Ks 67431 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>112</u> ft. ELEVATION:
--	--

Depth(s) Groundwater Encountered 1 ft. 102 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 63 1/2 ft. below land surface measured on mo/day/yr 3 / 11 / 02

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 15+ gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter. 9 in. to 112 ft., and. in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes. No. * ; If yes, mo/day/yrs sample was submitted
 Water Well Disinfected? Yes * No

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	CASING JOINTS: Glued. * Clamped.
2 PVC	4 ABS	7 Fiberglass		Welded
				Threaded.

Blank casing diameter 5 in. to 112 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface. 1.6 in., weight 2.00 lbs./ft. Wall thickness or gauge No. 2.50

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
			9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	ft.

SCREEN-PERFORATED INTERVALS: From. 92 ft. to 112 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From. 24 ft. to 112 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From. 3 1/2 ft. to 24 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? WEST NORTHWEST APPROX How many feet? 150

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	8	BROWN SANDY CLAY	81	89	GRAY SHALE
8	20	LITE COLOR LIMESTONE	89	97	DARK LIMESTONE & FLINT ROCK
20	30	LITE COLOR CLAY & SHALE	97	105	LITE COLOR LIMESTONE
30	31	LITE COLOR LIMESTONE	105	112	DARK BLUE & GRAY LIMESTONE & FLINT ROCK
31	32	LITE COLOR SHALE & CLAY			
32	33	LITE COLOR LIMESTONE			
33	36	LITE GRAY CLAY & SHALE			
36	38	GRAY SHALE			
38	60	LITE COLOR LIMESTONE			
60	61	HARD GRAY SHALE			
61	66	GRAY SHALE			
66	69	GRAY LIMESTONE			
69	75	LITE COLOR LIMESTONE			
75	81	DARK LIMESTONE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3 / 11 / 02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 397 This Water Well Record was completed on (mo/day/yr) 3 / 12 / 02 under the business name of CENTRAL KANSAS DRILLING by (signature) Herold D. Martin