COCATION OF WATER WELL:   Fraction   SW   NW   NW   V   Section Number   Township Number   Range Number   12 s   4 E   E   Section Number   Township Number   Range Number   12 s   4 E   E   Section Number   Township Number   T
Sweary   S
WATER WELL OWNER: KDHE RR#, St. Address, Box # 1000 SW Jackson Blvd City, State, ZIP Code Topeka KS  LOCATE WELL'S   DEPTH OF COMPLETED WELL   52.7   ft.   DOCATON WITH AN "X" IN SECTION BOX:  N
Carlet within trip: volumer: volumer: volumer: work within trip: volumer: volumer: volumer: work within trip: volumer:
Datum: NAVD 83   Datu
RR#, St. Address, Box # : 1000 SW Jackson Blvd City, State, ZIP Code City, State, ZIP Code City, State, ZIP Code City, State, ZIP Code Code Code Code Code Code Code Code
City, State, ZIP Code  LOCATE WELL'S  LOCATON WITH AN "X" IN SECTION BOX:  N  SECTION BOX:  Pump test data: Well water was Pump test data: Well water was Section A Industrial 7 Domestic (lawn & garden)  1 Domestic 3 From 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)  2 Irrigation 4 In, Dia 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)  1 Steel 3 Stanless steel 5 Fiberglass  Blank casing diameter 2 in. to 27.7 fi., Dia in. to ft.  2 SCREEN OR PERFORATION MATERIAL:  1 Continuous slot 3 Stanless steel 5 Fiberglass  SCREEN OR PERFORATION ATERIAL:  1 Continuous slot 3 Stanless steel 6 Concrete tile 8 RM (SR)  1 Continuous slot 3 Stanless steel 5 Fiberglass  SCREEN-PERFORATION OPENINGS ARE:  1 Continuous slot 3 Stanless steel 5 Fiberglass  SCREEN-PERFORATION OPENINGS ARE:  1 Continuous slot 3 Stanless steel 5 Fiberglass  SCREEN-PERFORATION OPENINGS ARE:  1 Continuous slot 5 Gauze wrapped  2 Louvered shutter 4 Key punched 6 Wire wrapped  3 CREED-PERFORATION OPENINGS ARE:  1 Continuous slot 5 Gauze wrapped  2 Louvered shutter 4 Key punched 6 Wire wrapped  3 CREED-PERFORATION OFENINGS ARE:  1 Continuous slot 5 Gauze wrapped  2 Louvered shutter 5 From 27 ft. ft. to 52.9 ft. From ft. to
LOCATON WITH AN "X" IN SECTION BOX:  N SECTION BOX: N SECTION SECTION SECTION SECTION MATERIAL: 1 Section Section Section Section Security Secur
Depth(s) Groundwater Encountered 1  SECTION BOX:  N  WELL'S STATIC WATER LEVEL Pump test data: Well water was ft. after hours pumping gpm Well water was ft. after hours pumping gpm Well WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 1 Steel 3 Stainless steel 5 Fiberglass 1 Casing height below land surface 0.24 ft., Weight 1 lbs./ft. Wall thickness or gauge No. 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 2 CREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 5 CREEN-PERFORATED INTERVALS: From 27.7 ft. to 52.9 ft. From ft. to ft. Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify 2 Sewert lines 5 Cess pool 8 Sewage lagoon ft. Field Standard water well below)
SECTION BOX:    N
SECTION BOX:    N
Pump test data: Well water was fi. after hours pumping gpm Well water supply 9 Dewatering 12 Other (Specify below) Water Well Disinfected? Yes No X ; If yes, mo/day/yrs Water Well Disinfected? Yes No X water Well Disinfected? Yes No X if yes, mo/day/yrs Water Well Disinfected? Yes No X if yes, mo/day/yrs Water Well Disinfected? Yes No X if yes, mo/day/yrs Water Well Disinfected? Yes No X if yes, mo/day/yrs Water Well Disinfected? Yes No X if yes, mo/day/yrs Water Well Disinfected? Yes No X if yes, mo/day/yrs Water Well Disinfected? Yes No X if yes, mo/day/yrs Water Well Disinfected? Yes No X if yes, mo/day/yrs Water Well Disinfected? Yes No X if yes, mo/day/yrs Water Well Disinfected? Yes No X if yes, mo/day/yrs Well Disinfected? Yes No X if yes, mo/day/yrs Well Disinfected? Yes No X if yes, mo/day/yrs Well Disinfected? Yes No X i
WELL WATER TO BE USED AS: 5 Pithlic water supply 9 Dewatering 12 Other (Specify below) 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) (1) Monitoring well  Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs Water Well Disinfected? Yes No X Sample was submitted  Type OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped  Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded  Threaded X Stank casing diameter 2 in. to 27.7 ft., Dia in. to ft., Dia in. to ft.  Casing height below land surface 0.24 ft., Weight Ibs./ft. Wall thickness or gauge No.  Type OF SCREEN OR PERFORATION MATERIAL: 1 Neat cement 2 Cement grout GRAVEL PACK INTERVALS: From 27.7 ft. to 52.9 ft. From ft. to ft.  GRAVEL PACK INTERVALS: From 27 ft. From ft. to ft. From ft. to ft.  Grout Intervals From 25 ft. to 27 ft. From ft. to ft. From ft. to ft.  Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 14 Abandoned water well below)  Dewatering 12 Other (Specify below) Mater with population of the concentration of th
WELL WATER TO BE USED AS: 5 Pithlic water supply 9 Dewatering 12 Other (Specify below) 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) (1) Monitoring well  Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs Water Well Disinfected? Yes No X Sample was submitted  Type OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped  Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded  Threaded X Stank casing diameter 2 in. to 27.7 ft., Dia in. to ft., Dia in. to ft.  Casing height below land surface 0.24 ft., Weight Ibs./ft. Wall thickness or gauge No.  Type OF SCREEN OR PERFORATION MATERIAL: 1 Neat cement 2 Cement grout GRAVEL PACK INTERVALS: From 27.7 ft. to 52.9 ft. From ft. to ft.  GRAVEL PACK INTERVALS: From 27 ft. From ft. to ft. From ft. to ft.  Grout Intervals From 25 ft. to 27 ft. From ft. to ft. From ft. to ft.  Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 14 Abandoned water well below)  Dewatering 12 Other (Specify below) Mater with population of the concentration of th
W SE   1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatching well 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) (10) Monitoring well   2 Irrigation 4 Industrial 7 Domestic (lawn & garden) (10) Monitoring well   2 Irrigation 4 Industrial 7 Domestic (lawn & garden) (10) Monitoring well   3 Kmp (sr) 4 Industrial 7 Domestic (lawn & garden) (10) Monitoring well   3 Kmp (sr) 4 Industrial 7 Domestic (lawn & garden) (10) Monitoring well   3 Kmp (sr) 4 Industrial 7 Domestic (lawn & garden) (10) Monitoring well   3 Kmp (sr) 5 Kmp (smp)   4 Industrial 7 Domestic (lawn & garden) (10) Monitoring well   3 Kmp (sr) 5 Kmp (smp)   5 Kmp (smp)
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs No X and was submitted to Department? Yes No X; If yes, mo/day/yrs No X and was submitted to Department? Yes No X and X and Yes No X a
Sample was submitted Water Weir Districted: Casing Joints: Glued Clamped  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded  2 PVC 4 ABS 7 Fiberglass Blank casing diameter 2 in to 27.7 ft., Dia in to ft., Dia in. to ft.  2 asing height below land surface 0.24 ft., Weight Ibs./ft. Wall thickness or gauge No.  2 PYPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass (7) PVC  2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR)  5 CREEN OR PERFORATION OPENINGS ARE:  1 Continuous slot (3) Mill slot 5 Gauze wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 5 CREEN-PERFORATED INTERVALS: From 27.7 ft. to 52.7 ft. From ft. to ft.  From ft. to ft. From ft. to ft.  GRAVEL PACK INTERVALS: From 27 ft. to 52.9 ft. From ft. to ft.  From ft. to ft.
Sample was submitted Water Weir Districted: Casing Joints: Glued Clamped  Type of Casing Used: 5 Wrought Iron 9 Other (specify below) Welded  Threaded X  Threaded X  Slank casing diameter 2 in to 27.7 ft., Dia in to ft., Dia in to ft.  Casing height below land surface 0.24 ft., Weight 1bs./ft. Wall thickness or gauge No.  Casing height below land surface 0.24 ft., Weight 1bs./ft. Wall thickness or gauge No.  Type of Screen or Perforation Material: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR)  SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 5 Concrete in the from 1 ft. to ft. From 1 ft. To f
Sample was submitted Water Weir Districted: Casing Joints: Glued Clamped  5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded  2 PVC 4 ABS 7 Fiberglass  Blank casing diameter 2 in to 27.7 ft., Dia in to ft., Dia in to ft.  Casing height below land surface 0.24 ft., Weight  TYPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 7 PVC  2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR)  1 Steel 3 Stainless steel 5 Fiberglass 7 PVC  2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR)  1 Continuous slot 3 Mill slot 5 Gauze wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 5 CREEN-PERFORATED INTERVALS: From 27.7 ft. to 52.7 ft. From ft. to ft. F
TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOTATION Welded  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded  2 PVC 4 ABS 7 Fiberglass 7 Fiberglass 3 In. to 27.7 ft., Dia in. to ft. Dia in. to ft.  Casing height below land surface 0.24 ft., Weight Ibs./ft. Wall thickness or gauge No.  TYPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR)  SCREEN OR PERFORATION OPENINGS ARE:  1 Continuous slot 3 Mill slot 5 Gauze wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 5 Louvered shutter 4 Key punched 6 Wire wrapped 5 SCREEN-PERFORATED INTERVALS: From 27.7 ft. to 52.7 ft. From ft. to ft. From ft. From ft. From ft. To ft. From ft. To ft. From
Casing diameter   2   in. to   27.7   ft., Dia   in. to   ft., Dia   in. to   ft.
Casing diameter   2   in. to   27.7   ft., Dia   in. to   ft., Dia   in. to   ft.
2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Mill slot 5 Gauze wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 27.7 ft. to 52.7 ft. From ft. to ft. Fro
2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Mill slot 5 Gauze wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 27.7 ft. to 52.7 ft. From ft. to ft. From
2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Mill slot 5 Gauze wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 27.7 ft. to 52.7 ft. From ft. to ft. Fro
2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Mill slot 5 Gauze wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 27.7 ft. to 52.7 ft. From ft. to ft. Fro
2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Mill slot 5 Gauze wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 27.7 ft. to 52.7 ft. From ft. to ft. Fro
SCREEN OR PERFORATION OPENINGS ARE:  1 Continuous slot 3 Mill slot 5 Gauze wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)  SCREEN-PERFORATED INTERVALS: From 27.7 ft. to 52.7 ft. From ft. to ft. From ft. From ft. To ft. From
2 Louvered shutter   Rey punched   Wife Wappeur   SCREEN-PERFORATED INTERVALS: From
2 Louvered shutter
GRAVEL PACK INTERVALS: From 27 ft. to 52.9 ft. From ft. to ft. From ft. From ft. To ft. From ft. Fro
GRAVEL PACK INTERVALS: From 27 ft. to 52.9 ft. From ft. to ft. From ft. From ft. To ft. From ft. Fro
From It. to It. Trom  6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete: 0-25ft  Grout Intervals From 25 ft. to 27 ft. From ft. to ft. From ft. to ft. From ft. to ft.  What is the nearest source of possible contamination:  1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify below)  2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well below)
Grout Intervals From 25 ft. to 27 ft. From ft. to ft. From ft. ft. From ft. to ft. From ft. ft. ft. ft. From ft. ft. ft. ft. From ft.
What is the nearest source of possible contamination:  1 Septic tank 2 Sewer lines 5 Cess pool 8 Sewage lagoon 1 Total  1 Livestock pens 1 Insecticide Storage 1 Abandoned water well 1 below 1 Severy lines 1 Cess pool 1 Fuel storage 1 Abandoned water well 1 Septic tank 2 Sewer lines 3 Cess pool 1 Fuel storage 1 Abandoned water well 1 Septic tank 3 Cess pool 4 Cess pool 5 Cess pool 8 Sewage lagoon 1 Fuel storage 1 Abandoned water well 1 Septic tank 3 Cess pool 8 Sewage lagoon 1 Septic tank 9 Cess pool 1 Septi
What is the nearest source of possible contamination:  1 Septic tank 2 Sewer lines 5 Cess pool 8 Sewage lagoon 1 Total  1 Livestock pens 1 Insecticide Storage 1 Abandoned water well 1 below 1 Severy lines 1 Cess pool 1 Fuel storage 1 Abandoned water well 1 Septic tank 2 Sewer lines 3 Cess pool 1 Fuel storage 1 Abandoned water well 1 Septic tank 3 Cess pool 4 Cess pool 5 Cess pool 8 Sewage lagoon 1 Fuel storage 1 Abandoned water well 1 Septic tank 3 Cess pool 8 Sewage lagoon 1 Septic tank 9 Cess pool 1 Septi
1 Septic tank 2 Sewer lines 4 Lateral lines 7 Pit privy 5 Cess pool 8 Sewage lagoon 1 Livestock pens 1 Insecticide Storage 14 Abandoned water well 15 Cess pool 16 Other (specify below)
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pells 13 Insectional States 14 Abandoned water well 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well below)
Sewer lines 5 Cess poor 8 Sewage ingoon Cyrun 11/2 and 11
5 Watertight sewer intes o boopage par > 2 - 5 - 5 - 5 - 5 - 5 - 5 - 5 - 5 - 5 -
Direction from wor. At 10 CCINC INTERVALS
FROM TO LITHOLOGIC LOG TROTT
0 20 Brown, medium, sandy clay
20 25 Gray shale
25 32 Tan shale
32 52.9 Hard Limestone
, c porr
Flushmount waiver from BOW
1) Conference or (3) physical (2) become trusted or (3) physical
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) onstructed, (2) econstructed, or (3) plugged and this record is true to the best of my knowledge and believed to the best of my knowledge and believed to the best of my knowledge and believed to the best of my knowledge.
lunder my jurisdiction and was completed on (mo/day/year) 11/17/12 and the 11/29/12
Kansas Water Well Contractor's License No. 757 . This water well keeping to by (signature)
under the business name of Larsen & Associates, Inc. by (signature)  INSTRUCTIONS: Please in blanks or circle the correct answers. Send top three copies to Kansas Department of this th and Environment. Bureau of Water,  INSTRUCTIONS: Please in blanks or circle the correct answers. Send top three copies to Kansas Department of this th and Environment. Bureau of Water,  INSTRUCTIONS: Please in blanks or circle the correct answers. Send top three copies to Kansas Department of this th and Environment. Bureau of Water,  INSTRUCTIONS: Please in blanks or circle the correct answers. Send top three copies to Kansas Department of this than department of the correct answers. Send top three copies to Kansas Department of this than department of the correct answers.
INSTRUCTIONS: Please fill in blanks or circle the correct answers. Send top three copies to Kansas Department of Angula and Elivironment. Bureau of Williams Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WILL OWNER and retain one for Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WILL OWNER and retain one for the section of
Geology Section, 1000 SW Jackson St., Suite 420, Topicka, Kansas Good Jackson St., Suite 420, Topicka, Kansas G