WATER WELL RECORD FOR MING 5 PRIMITAL 956						
Original Record Correction Change in Well Use Resources App. No. Well ID						
1 LOCATION OF W.		Fraction		ction Numb $ u 2$	per Township Numb	
County: Co. WWA SWASWA 1/4 V2 T 120 R 4 FE I W 2 WELL OWNER: Last Name: Sholar First: Dale Street or Rural Address where well is located (if unknown, distance and						
Address: PO, Box 477 direction from nearest town or intersection): If at owner's address, check here: I form J.C. Go Wist 3 Mills on 18 May						
City: Chapman State: HS ZIP: 67431 To M. Word LIKE RIF GO Mile South						
3 LOCATE WELL 4 DEPTH OF COMPLETED WELL: 120						
WITH "X" IN	Depth(s) Groundwate	er Encountered: 1)	. / 1	L 5 Lati	iudey. D.J	(decimal degrees)
SECTION BOX:	Depth(s) Groundwater Encountered: 1) 6 9					
	WELL'S STATIC WATER LEVEL: S.O.I. Source for Latitude/Longitude:					
NWNE above land surface, measured on (mo-day-yr) (WAAS enabled? Yes Pump test data: Well water was ft. Land Survey Topographic N						
W E	E after hours pumping gpm					
Well water was ft. after hours pumping gpm 6 Flevation: 123 4 ft Ground Level TOC						
	Estimated Yield:	5 gpm				Ground Level 🔲 TOC
S mile	Bore Hole Diameter:	.9 in. to .1.20.		Sour		GPS ☐ Topographic Map
7 WELL WATER TO BE USED AS:						
I. Dorpestic: 5. Public Water Supply: well ID						
Household		ring: how many wells?			Hole: well ID	
☐ Lawn & Garden ☐ Livestock						
2. Irrigation	Irrigation 9. Environmental Remediation: well ID					
3. Feedlot						
4. Industrial Recovery Injection 13. Other (specify):						
Was a chemical/bacteriological sample submitted to KDHE? Yes Yes No If yes, date sample was submitted:						
8 TYPE OF CASING USED: Steel PPVC Other CASING JOINTS: Glued Clamped Welded Threaded						
Casing diameter 5 in. to						
Casing height above land surface						
Steel Stainless Steel Fiberalss DrVC Other (Specify)						
☐ Brass ☐ Galvanized Steel ☐ Center tile ☐ None used (open hole)						
SCREEN OR PERFORATION OPEN ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify)						
☐ Continuous Slot						
SCREEN-PERFORATED INTERVALS: From						
GRAVEL PACK INTERVALS: From						
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other						
Nearest source of possible contamination:						
☐ Septic Tank	Lateral Li		_	Livestock P	_	cide Storage
☐ Sewer Lines ☐ Watertight Sewer Lin	☐ Cess Pool nes ☐ Seepage F	–		Fuel Storag Fertilizer St		oned Water Well
☐ Other (Specify)	. ۵۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰					on out won
Other (Specify) Direction from well? Distance from well? Ithough To LITHOLOGIC LOG FROM TO LITHOLOG (cont.) or PLUGGING INTERVALS						
10 FROM TO	TOP Soil	OGIC LOG	FROM 92/	TO 9/	11	r PLUGGING INTERVALS
1 4	3 Brown Clay		96	1/13	Ling love	1.6
3 7	Vellow Sh	als	103	120	Linestend	
7, 16	Limistore			, , ,		
21 32	Vellow Shr			-		
32 69 Brown Shale Notes:					<u> </u>	
69 80 Limistone (WATER)						
80 99 Brown Shale						
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year)						
Kansas Water Well Con	ntractor's License No.		ater Well Re	cord was co	mpleted on (mo-day-y	(ear) 6/21 /2017
under the business name	e of Halfleman	I WIN DO	Wing		win the	
Mail 1 white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment and Envi						
Visit us at http://www.kdheks.gov/waterwell/index.html KSA 82a-1212 Revised 1/20/2015						