WATER	R WELL	RECORD	Form WWC-5	Divis	ion of Wa	ter Reso	urces: App. No.			
County	(WATER WELL: Geary	SW % NE %	NE 3.	11		Township Number	R 5 E		
Distance and direction from nearest town or city street address of well if Global Positioning System (decimal degrees. min. of 4 digits)										
located within city? Latitude: N 39°01'38.3"										
539 W 6 th St., Junction City Longitude: W 96°50'18.8" 2 WATER WELL OWNER: Leiszler Oil Co. Elevation: 1111.87 pin / 1111.53 toc										
2 WATER WELL OWNER: Leiszler Oil Co. Elevation: 1111.87 pin / 1111.53 toc										
	RR#, St. Address, Box # : 635 W Crawford						Datum: Above mean sea level			
City, State, ZIP Code : Clay Center, KS 67432 Data Collection Method: legal survey										
3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL 50 ft.										
LOCA				ľ	MW13			_		
1	AN "X" I	N Depth(s) Grou	ndwater Encountered 1	- 		_ ft. 2 _	ft. 3	ft.		
SECT	WITH AN "X" IN Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 SECTION BOX: WELL'S STATIC WATER LEVEL 45.00 ft. below land surface measured on mo/day/yr 3/26/0'									
N Pump test data: Well water was ft. after hours pumping gpr Est. Yield gpm: Well water was ft. after hours pumping gpr										
Est. Yield gpm: Well water was ft. after hours pumping gpm										
- N/A	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well									
1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below										
W E Domestic Feet for 0 of herd water supply Dewatering 12 of the (Speetly Settlett) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) (10) Monitoring well										
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs										
was a chemical bacter to logical sample submitted to Department: 1 es 140 A, 11 yes, morally yes										
S Sample was submitted Water Well Disinfected? Yes No X										
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped										
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded										
2) PVC 4 ABS 7 Fiberglass Threaded X										
2 PVC 4 ABS 7 Fiberglass Threaded X Blank casing diameter 2 in. to 50 ft., Dia in. to ft., Dia in. to ft. Casing height below land surface 0.34 ft., Weight lbs./ft. Wall thickness or gauge No.										
Cosing height helpsy land surface 0.34 ft Weight lbc/ft Well thickness or gauge No.										
Casing neight below land surface 0.54 It., weight 105./IT. Wall thickness of gauge No.										
1 Steel 2 Steinless steel 5 Fibergless (7) DVC 0 ABS 11 Other (specific)										
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass (7) PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)										
1 Continuous slot (3) Mill slot 5 Guaze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)										
1 Continuous slot 3 Mill slot 5 Guaze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)										
SCREEN-PERFORATED INTERVALS: From 35 ft. to 50 ft. From ft. to ft.										
From ft. to ft. From ft. to ft.										
GRAVEL PACK INTERVALS: From 33 ft. to 50 ft. From ft. to										
	2112221710	on in the tribes.	From	ft to		ft Fr	rom ft	to ft.		
From ft. to ft. From ft. to ft.										
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other cement, 0-2'										
Grout Intervals From 2 ft. to 33 ft. From ft. to ft. From ft. to ft.										
What is the nearest source of possible contamination:										
	tic tank			10 Livestoc			ecticide Storage	16 Other (specify		
1	er lines	5 Cess poo					andoned water well	below)		
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/ gas well										
Direction	from well?			How many:	feet?					
FROM	TO	ודטר	LOGIC LOG	FROM	TO	T	LITHOLOGI	CLOG		
0	3	Soil	TOGIC TOG	33	35	Sand	with silt and trace c			
3	14		rown, very stiff, dry	33	33		d brown	mj, non smining,		
14	15.5		ne, iron staining, dry,	38	40		with silt and trace c	lay, iron staining		
17	13.3	trace silt	ne, non stanning, dry,	30	70	very n		inj, iron stanning,		
15.5	18	Silt, gray-brown,	very hard, dry	43	45	Sand	with silt and trace c	lay, iron staining.		
18	20		rown to brown, trace	+-3-	73		noist to slightly wet			
	20	iron staining, dry		-		1 21 9 11	TO STEATE WATER			
23	25		ed-brown, trace iron			1				
		staining, dry, fine				Flush	mount waiver by D.	Taylor		
33	35	Sand with silt and				-				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged										
under my jurisdiction and was completed on (mo/day/year) 3/23/07 and this record is true to the best of my knowledge and belief.										
Kansas Water Well Contractor's License No. 757 . This Water Well Record was completed on (mo/day/year) 4/12/07										
under the business name of Larsen & Associates, Inc. by (signature)										
INSTRUCTIONS: Please fill in blanks or circle the correct answers. Send too three copies to Kansas Department of Health and Environment, Bureau of Water,										
Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for										
your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell.										