WATER WELL RECORD Form WWC-5 Division of Water Resources; App. No.
1 LOCATION OF WATER WELL: Fraction Section Number Township Number Range Number
County: Geary NE ½ NE ½ NE ½  Distance and direction from nearest town or city street address of well if Global Positioning System (decimal degrees, min. of 4 digits)
located within city? Latitude: N 39.02886°
539 W 6 <sup>th</sup> St, Junction City Longitude: W 96.83692°
2 WATER WELL OWNER: Leiszler Oil Co.  RR#, St. Address, Box # : 635 W Crawford  Elevation: 1104.87 pin / 1104.52 toc  Datum: Above mean sea level
RR#, St. Address, Box # : 635 W Crawford City, State, ZIP Code : Clay Center, KS 67432  Datum: Above mean sea level Data Collection Method: legal survey
3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL 46.5 ft.
LOCATON MW23
WITH AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 34.66 ft. below land surface measured on mo/day/yr 2/26/08
SECTION BOX: WELL'S STATIC WATER LEVEL 34.66 ft. below land surface measured on mo/day/yr 2/26/08
N Pump test data: Well water was ft. after hours pumping gpm
X   Est. Yield gpm: Well water was ft. after hours pumping gpm
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
W   1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
SW — SE —   2 Imgation 4 industrial 7 Domestic (lawn & garden) (to) Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs
Sample was submitted  Water Well Disinfected? Yes  No X
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
(2) PVC 4 ABS 7 Fiberglass Threaded X
Blank casing diameter 2 in. to 31.5 ft., Dia in. to ft., Dia in. to ft.
(2) PVC 4 ABS 7 Fiberglass Threaded X Blank casing diameter 2 in. to 31.5 ft., Dia in. to ft., Dia in. to ft.  Casing height below land surface 0.35 ft., Weight lbs./ft. Wall thickness or gauge No.
TYPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass (7) PVC 9 ABS 11 Other (specify)  2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)
1 Steel 3 Stainless steel 5 Fiberglass (7) PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Congrete tile 8 PM (SP) 10 Ashertes Comput 12 None year (specify)
1 Continuous slot (3) Mill slot 5 Guaze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 31.5 tt. to 46.5 ft. From tt. to tt.
GRAVEL PACK INTERVALS: From 30 ft to 465 ft From ft to ft.
2 Louvered shutter & Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)  SCREEN-PERFORATED INTERVALS: From 31.5 ft. to 46.5 ft. From ft. to ft.  From ft. to ft.  GRAVEL PACK INTERVALS: From 30 ft. to 46.5 ft. From ft. to ft.  From ft. to ft.  From ft. to ft.  From ft. to ft.
6 CROUT MATERIAL 1 Next coment 2 Coment group (2 Posterite (4) Other coment 0.22
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other concrete, 0-2' Grout Intervals From 2 ft. to 30 ft. From ft. to ft. From ft. to ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify
2 Sewer lines 5 Cess pool 8 Sewage lagoon (1) Fuel storage 14 Abandoned water well below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/ gas well
Direction from well? Southwest How many feet? ~675
FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG
0 0.5 Asphalt 25 27 Sand, fine to medium grained, trace clay,
5 7 Silty-clay, light brown, moist, no very moist, no petroleum odor petroleum odor 30 32 Sand, fine to medium grained, trace clay,
10 12 Silty-clay with fine sand, light brown, very moist to wet, no petroleum odor
moist, no petroleum odor 35 37 Sand, fine to medium grained, trace clay,
12.5 Increase in sand content, very moist wet to saturated, no petroleum odor
15 17 Sand, fine to medium grained, trace clay, very moist to wet, no petroleum odor
20 22 Sand, fine to medium grained, trace clay, Flushmount waiver with Bureau of Water
very moist, no petroleum odor
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged
under my jurisdiction and was completed on (mo/day/year)  Kansas Water Well Contractor's License No.  757  This Water Well Record was completed on (mo/day/year)  3/19/08
under the business name of Larsen & Associates, Inc.    Inis water well Record was completed on (inorday/year)   3/19/08
INSTRUCTIONS: Please fill in blanks or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water.
Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send and to WATER WELL OWNER and retain one for