


1] LOCATION OF WATER WELL: County: Geary Fraction: SW 1/4 NE 1/4 NW 1/4 Section Number: 13 Township Number: T 12 S Range Number: R 5 E

Distance and direction from nearest town or city street address of well if located within city?
901 S. Washington, Junction City, Ks

2] WATER WELL OWNER: Robo Car Wash
 RR#, St. Address, Box #: 901 S. Washington Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Junction City, Ks Application Number:

3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4] DEPTH OF COMPLETED WELL: 34 ft. ELEVATION: ft.

Depth(s) Groundwater Encountered: 1. 26 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL: 28.01 ft. below land surface measured on mo/day/yr 11-3-94
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter: 8.625 in. to 34 ft., and in. to ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well mw-4A
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No X

5] TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded X

Blank casing diameter: 2 in. to 19 ft., Dia. in. to ft., Dia. in. to ft.
 Casing height above land surface: 0 in., weight Sch. 40 lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 2 Mill slot 3 Gauzed wrapped 4 Saw cut 5 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 19 ft. to 34 ft., From ft. to ft., From ft. to ft.
 SAND
 GRAVEL PACK INTERVALS: From 18 ft. to 34 ft., From ft. to ft., From ft. to ft.

6] GROUT MATERIAL: 2 Neat cement 3 Cement grout 4 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 16 ft., From 16 ft. to 18 ft., From ft. to ft.

What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Contaminated site
 13 Insecticide storage

Direction from well? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5	Asphalt			
0.5	8.5	Silty clay			
8.5	18.5	clayey silt			
18.5	22.0	Silty clay			
22.0	23.0	SAND			
23.0	34.0	SAND			
34.0	TO				

FLUSH MOUNT WAIVER
 Oct 17-94
 DON TAYLOR

7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-31-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 479 This Water Well Record was completed on (mo/day/yr) 12-02-94 under the business name of EBBERTS DRILLING by (signature) Shogon Ebberts