				WELL RECORD	Form WWC-5	***************************************	2a-1212			
	ON OF WAT	ER WELL:	Fraction	יידר אי		tion Numbe	'	· · · · · · · · · · · · · · · · · · ·		
County:		fuere manual Annua	SW 1/4		SE 1/4	24	T 12	S R 7 EW		
Distance a	na airection	_	•	lress of well if locate	•					
- T			$\frac{1}{3}$, $\frac{1}{4}$ s	outh of Junc	tion City	•				
recently the second	R WELL OW									
RR#, St. Address, Box # : Rt. 1 Box 235 Ray's job							Board of Agriculture, Division of Water Resource			
	, ZIP Code		d, KS 665				Application Nu	AND THE PROPERTY OF THE PROPER		
3 LOCATE	WELL'S LO	CATION WITH 4	DEPTH OF CO	MPLETED WELL	. 150!	ft. ELE\	/ATION:			
' AN "X"	IN SECTION	BOX: De	pth(s) Groundwa	ater Encountered	1 3.7. !	<i>.</i> ft	. 2	ft. 3		
ī [I	I WE	ELL'S STATIC V	VATER LEVEL 2	.6 ! ft. t	elow land s	urface measured on mo	o/day/yr2-25-92		
	1	·						iours pumping gpr		
-	- NW	NE Es	. Yield $2\frac{1}{2}$ gpm: Well water was ft. after hours pumping gpr							
			re Hole Diameter 8.3/4in. toft., andin. to							
N =		AND THE PROPERTY OF THE PROPER		BE USED AS:	5 Public water supply6 Oil field water supply8 Air conditioning9 Dewatering			ng 11 Injection well		
,	ı	k	1 Domestic	3 Feedlot			•			
	- SW	SE	2 Irrigation	4 Industrial						
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well										
į L		manuscriptor in consistent constraints	tted	oteriological sample	Submitted to D	•	Vater Well Disinfected?			
E TVDE C	7E DI VVIK O	ASING USED:		5 Wrought iron	8 Concr			S: Glued X Clamped		
				-				Welded		
1 Ste		3 RMP (SR)		6 Asbestos-Cement		(specify bel	· ·	Threaded		
2 PV	<u> </u>	4 ABS	0.30	7 Fiberglass		50_11	Q 4 D: 5"	in. to .130-150		
_	-			1., weight				gauge No. •258		
	TYPE OF SCREEN OR PERFORATION MATERIAL:					<u>'C</u>	10 Asbestos-cement			
1 Ste		3 Stainless st		5 Fiberglass		MP (SR)	11 Other (specify)			
2 Bra		4 Galvanized						12 None used (open hole)		
SCREEN (OR PERFOR	IATION OPENINGS	ARE:	5 Gau	5 Gauzed wrapped		8 Saw cut	11 None (open hole)		
1 Co	ntinuous slo	: 3 Mill s	lot	6 Wire	wrapped		9 Drilled holes			
2 Lo	uvered shutte	er 4 Key p		7 Torc			()			
SCREEN-	PERFORATE	D INTERVALS:						ft. to		
								ft. to		
9	GRAVEL PAG	CK INTERVALS:	From 2.4	ft. to .	150	ft., F	rom	ft. to		
			From	ft. to		ft., F	rom	ft. to		
6 GROUT	MATERIAL			Cement grout						
Grout Inter	vals: Fron	nft.	to24	ft., From	ft.	to	ft., From	ft. to		
What is the	e nearest so	urce of possible cor	ntamination:	n:			estock pens	14 Abandoned water well		
1 Se	ptic tank	4 Lateral li				11 Fuel storage		15 Oil well/Gas well		
2 Se	wer lines	5 Cess po	ol	8 Sewage lag	goon	12 Fertilizer storage		16 Other (specify below)		
3 Wa	atertight sew	er lines 6 Seepage	pit 9 Feedyard			13 Insecticide storage				
Direction f	rom well?	east		·			How many feet? 165			
FROM	то		LITHOLOGIC L	OG	FROM	то		GGING INTERVALS		
0	17	Clay-Brown			102	113	Shale-Grey			
17	21	Limestone-			113	116	Limestone-Tar	1		
21	36	Shale-Grey			116	119	Gyp			
36	39	Limestone-		ose	119	150	Shaley Limest	cone-Grey		
39	55	Limestone-								
55	62	KXXXX Shale						P. 100-101		
62	64							A A A A A A A A A A A A A A A A A A A		
64	69	Limestone-Grey Shale-Grey								
69	I I	Shale-Red								
	75									
75	81	Gyp Limograpa Cray				1				
81	85	Limestone-Grey Shale-Grey						A A A A C V WOOD MADE		
85	94									
94	98					-				
98_	101	Shale-Grey								
101	l 102 l	Limestone-	_			1				
								gged under my jurisdiction and w		
completed	on (mo/day/	year) 2	-25-92			and this re	cord is true to the best	of my knowledge and belief. Kans		
i							ed on (mo/day/y)) 3	· <i>V</i> // 8		
			דוומת משת	ING CO., INC		by (sig	nature) X A U	O IIA la sa ua		