


1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 SE 1/4 Section Number 13 Township Number T 12 S Range Number R 7 E
 County: GEARY

Distance and direction from nearest town or city street address of well if located within city?
FROM JUNCTION CITY: 9 MILES EAST ON I-70, 4.5 MILES SOUTHWEST ON MCLOWELL CREEK RD.

2 WATER WELL OWNER: PAT SCHMIDT
 RR#, St. Address, Box #: 1704 HAYES DR Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: MANHATTAN, KS 66502 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL 142 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1 34 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 2.9 ft. below land surface measured on mo/day/yr 2/2/06
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 3/4 gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS:
 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 132 ft., Dia 5 in. to 42 ft., Dia in. to ft.
 Casing height above land surface 2.4 in., weight lbs./ft. Wall thickness or gauge No. 50R26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 42 ft. to 62 ft., From ft. to ft.
 From 132 ft. to 142 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 2.3 ft. to 14.2 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 23 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) OPEN PASTURE
 Direction from well? How many feet? NEW CONSTRUCTION

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	SOIL			
1	6	LEASTONIAN WHITE			
6	12	SHALE, GRAY			
12	14	LEASTONIAN WHITE			
14	22	SHALE, BROWN TO DK GRAY			
22	34	LEASTONIAN TAN			
34	48	SHALE, GRAY TO BLUE GRAY			
48	54	LEASTONIAN TAN			
54	128	SHALE, ALUMINATE COLORS			
128	132	GYP SUM			
132	142	SHALE, GRAY			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2/2/06 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 760 This Water Well Record was completed on (mo/day/yr) 2/2/06 under the business name of ASSOCIATED DRILLING INC. by (signature) [Signature]