WATER WELL RECORD	Form WWC	C-5		vision of Water Resources App. No.
1 LOCATION OF WATER WELL:	Fraction			on Number Township No. Range Number
County: WABAUNSEE	NW1/4 SE 1/4 SW 1/4			1/ T /2 S R 9 DE DW
Street/Rural Address of Well Location; if unknown, distance & direction				l Positioning System (GPS) information:
from nearest town or intersection: If at owner's address, check here \square . 5 WEST OF ALMA ON OLD K18				de: (in decimal degrees) tude: (in decimal degrees)
5 WEST OF ALMIA	ON OLD KIZ	<i>5</i>		tion: (in decimal degrees)
			Datum	1: WGS 84, NAD 83, NAD 27
2 WATER WELL OWNER: ROSS	YORDY		Collect	tion Method:
RR#, Street Address, Box #: 2908	4 GOOSENBERRY	/ KOAD		GPS unit (Make/Model:)
	1, US 66401			Digital Map/Photo, Topographic Map, Land Survey
	1,000 00 101	a descende to the complete special and a second	Est. Ac	<u>ccuracy</u> :
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF (COMPLETED WELL	10	0	ft.
				(2) ft. (3) ft.
N WELL'S STATIC WATER LEVEL\$. 8ft. below land surface measured on mo/day/yr/./				
Pump test data: Well water wasft. after hours pumping gpm				
EST. YIELD. 20. gpm. Well water was				
$\mathbf{w} \mid \mathbf{h} \mid $				
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well				
□ Domestic □ Feedlot □ Oil field water supply □ Dewatering □ Other (Specify below) □ Irrigation □ Industrial □ Domestic-lawn & garden □ Monitoring well □ LIVE STOCK				
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted				
1 mile Water well disinfected? Yes No				
5 TYPE OF CASING USED: Steel PVC Other				
CASING JOINTS: W Glued Clamped Welded Threaded Casing diameter in to ft Diameter in to ft				
Casing diameter				
TYPE OF SCREEN OR PERFORATION MATERIAL:				
Steel Stainless Steel PVC Other (Specify)				
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE:				
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole) Louvered shutter Key punched Wire wrapped Saw cut Other (specify)				
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From ft. to ft.				
From. ft. to ft., From ft. to ft.				
GRAVEL PACK INTERVALS:				ft., From ft. to ft.
				ft., From ft. to ft.
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other				
Grout Intervals: From				
What is the nearest source of possible contamination:				
Septic tank Lateral lin		Livestock		☐ Insecticide storage ☐ Other (specify below) ☐ Abandoned water well
Sewer lines Cesspool Watertight sewer lines Seepage		Fuel storag Fertilizer s		Oil well/gas well
Direction from well NONE RRESENT Distance from well				
FROM TO LITHOLOG		FROM	TO	LITHO. LOG (cont.) or PLUGGING INTERVALS
O 6 BROWN CLA	Y	60	88	GRAY SUALE
6 15 YELLOW SU		88	99	LIMESTONE
6 15 YELLOW SUL			100	GRAY SUALE
18 2 GIMESTONE				
21 35 GRAY SHALE				
	: &LIMESTONE			
38 42 GRAY SYALE				
42 46 LIMESTOWE	A Service of the Control of the Cont			
46 56 GRAY SUAL	Specification of the second of			
56 60 LIMESTUNE				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, constructed, or				
under my jurisdiction and was completed on (mo/day/year)//				
under the business name of	E VALLEY DON	LING A	ZYBG (~	signature)
INSTRUCTIONS: Use typewriter or ball point per				ease fill in blanks and check the correct answers. Send three copies
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.				
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html				

KSA 82a-1212

Original Returned to Sender