		WATER	WELL RECORD F	orm WWC-5	KSA 82a-	1212		
LOCATION OF	WATER WELL:	Fraction		Sec	tion Number	Township N	umber	Range Number
ounty: Bicki	nsen	NE 1/4	SE 1/4 NW	1/4	23	т 13	<u>s</u>	R I (B)
istance and dire	ction from nearest tov	wn or city street add	ress of well if located	within city?				
	Les East of S							
WATER WELL	OWNER: Bob Wi	ilsen Wilsen	Bres Liveste	ck				
	s, Box # : 501 S.					Board of A	Agriculture,	Division of Water Resourc
	ode : Abiler						n Number:	
LOCATE WELL	'S LOCATION WITH	4 DEPTH OF COI	MPLETED WELL	75	ft. ELEVA	ΓΙΟΝ:		
AN "X" IN SEC	N BOX:	Depth(s) Groundwa	iter Encountered 1.	65	ft. 2		ft. 3	3 <u>.</u>
· [ı	WELL'S STATIC W	ATER LEVEL 5	5 ft. b	elow land surf	ace measured or	n mo/day/yr	9 . / . 110 . / 88
, , , , , , , , , , , , , , , , , , ,	1 1	Pump t	est data: Well water	was	ft. at	ter	. hours pu	ımping gpr
	NE	Est. Yield 25+	gpm: Well water	was	ft. at	ter <u>.</u>	. hours pu	ımping gpr
<u> L i </u>		Bore Hole Diamete	r 9 in. to .	60		ind 5″. 3 0 🕻	in	to
w	i i	WELL WATER TO	BE USED AS: 5	Public water	r supply	8 Air conditioning	11	Injection well
sw		1 Domestic	3 Feedlot 6	Oil field wa	ter supply	9 Dewatering	12	Other (Specify below)
J 3W		2 Irrigation	4 Industrial 7	Lawn and	garden only	0 Monitoring we	ļ ,	
<u>l</u> i	1	Was a chemical/ba	cteriological sample su	bmitted to D	epartment? Ye	sNoీ	; If yes	, mo/day/yr sample was su
	S	mitted				er Well Disinfect		
TYPE OF BLA	NK CASING USED:	5	Wrought iron	8 Concre	ete tile	CASING JC	INTS: Glue	d .* Clamped
1 Steel	3 RMP (S	iR) (Asbestos-Cement	9 Other	(specify below)	Weld	ed
2 PVC	4 ABS	(a) 7	7 Fiberglass				Threa	aded
								in. to f
asing height abo	ove land surface	13:in	., weight	160	lbs./1	t. Wall thickness	or gauge N	o•21/4
YPE OF SCREE	N OR PERFORATIO	N MATERIAL:		7 PV	name .	10 As	oestos-ceme	ent
1 Steel	3 Stainles		Fiberglass	8 RM	IP (SR)	11 Oti	ner (specify)	
2 Brass	4 Galvaniz	zed steel 6	Concrete tile	9 AB	S	12 No	ne used (op	en hole)
CREEN OR PE	RFORATION OPENIN	IGS ARE:	5 Gauzeo	wrapped		8 Saw cut		11 None (open hole)
1 Continuou	is slot 3 M	fill slot	6 Wire w	rapped		9 Drilled holes		
2 Louvered	shutter 4 K	(ey punched	7 Torch o			• •	• •	
CREEN-PERFO	RATED INTERVALS:							o
								o
GHAVE	L PACK INTERVALS:							of
GROUT MATE	RIAL: 1 Neat	From	ft. to Cement grout		ft., Fron		11. 1	<u>o</u> f
								ft. to
	est source of possible		n., 110111		10 Livest			bandoned water well
	ik 4 Late		7 Pit privy					il well/Gas well
2 Sewer line	_		8 Sewage lagoo			zer storage		Other (specify below)
	t sewer lines 6 Seep	•	9 Feedyard			icide storage		
Direction from we		ougo pii	0 / 000,0.0			y feet? 90		
FROM TO		LITHOLOGIC LO	OG	FROM	то		LUGGING I	NTERVALS
0 3	SANDY CI	AY						
3 17	FINE SAN	130						
17 21								
21 28		D						
28 30	SANDY GI	AY						
30 43		ND .						
113 148								
18 52		& SHALE				·····		
52 53		IALE						
53 56		& SHALE						
56 59		Y CLAY						
	ROCK ROCK							
59 60		IE						
60 70				<u> </u>				
70 75		IALE			<u> </u>			
CONTRACTO	R'S OR LANDOWNE	R'S CERTIFICATION	N: This water well was	s (1) constru	cted, (2) reco	nstructed, or (3)	plugged und	der my jurisdiction and wa
ompleted on (ma	o/dav/vear) 9. 🎉 . 🕽	lo. //. 88			and this reco	d is true to the b	est of my kn	owledge and belief. Kansa
Vater Well Contri	actor's License No.	397	This Water We	Il Record wa	s completed of	on (mg/day/yr) .	9 1,30	√ 88
nder the busines	s name of CENTRA	AL KANSAS DRI	LLING		by (signat	ure) Haro	dN.	martin
				se fill in blanks				copies to Kansas Department
of Health and En	vironment, Bureau of Water	Protection, Topeka, Kansa	s 66620-7320. Telephone: 9	13-296-5514. Se	nd one to WATER	WELL OWNER and r	etain one for yo	our records.