

1 LOCATION OF WATER WELL: Fraction SW 1/4 NW 1/4 SW 1/4 Section Number 21 Township Number T 13 S Range Number R 1 (E)

Distance and direction from nearest town or city street address of well if located within city? 1/2 mile East of Solomon, Ks on Hwy 140 & 1/4 mile South & 1/2 mile East

2 WATER WELL OWNER: Wilson Bros. Livestock RR#, St. Address, Box #: 501 S Buckeye City, State, ZIP Code: Abilene, Kansas 67410 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram of section box with X in SW quadrant] 4 DEPTH OF COMPLETED WELL: 33 ft. ELEVATION: 10/11/88. WELL'S STATIC WATER LEVEL: 27 ft. below land surface measured on mo/day/yr 10/11/88. Pump test data: Well water was ... gpm after ... hours pumping ... gpm. Est. Yield: 20\* gpm. Well water was ... ft. after ... hours pumping ... gpm. Bore Hole Diameter: 9 in. to 33 ft., and ... in. to ... ft. WELL WATER TO BE USED AS: 5 Public water supply, 8 Air conditioning, 11 Injection well, 1 Domestic, 3 Feedlot, 6 Oil field water supply, 9 Dewatering, 12 Other (Specify below), 2 Irrigation, 4 Industrial, 7 Lawn and garden only, 10 Monitoring well. Was a chemical/bacteriological sample submitted to Department? Yes... No... If yes, mo/day/yr sample was submitted. Water Well Disinfected? Yes \* No

5 TYPE OF BLANK CASING USED: 1 Steel, 2 PVC, 3 RMP (SR), 4 ABS, 5 Wrought iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below), CASING JOINTS: Glued X Clamped, Welded, Threaded. Blank casing diameter: 5 in. to 33 ft., Dia. in. to ... ft., Dia. in. to ... ft. Casing height above land surface: 25 in., weight 160 lbs./ft. Wall thickness or gauge No. 214. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 2 Brass, 3 Stainless steel, 4 Galvanized steel, 5 Fiberglass, 6 Concrete tile, 7 PVC, 8 RMP (SR), 9 ABS, 10 Asbestos-cement, 11 Other (specify), 12 None used (open hole). SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 2 Louvered shutter, 3 Mill slot, 4 Key punched, 5 Gauzed wrapped, 6 Wire wrapped, 7 Torch cut, 8 Saw cut, 9 Drilled holes, 10 Other (specify), 11 None (open hole). SCREEN-PERFORATED INTERVALS: From 27 ft. to 33 ft., From ... ft. to ... ft., From ... ft. to ... ft. GRAVEL PACK INTERVALS: From 23 ft. to 33 ft., From ... ft. to ... ft., From ... ft. to ... ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other. Grout Intervals: From 1 ft. to 23 ft., From ... ft. to ... ft., From ... ft. to ... ft. What is the nearest source of possible contamination: 1 Septic tank, 2 Sewer lines, 3 Watertight sewer lines, 4 Lateral lines, 5 Cess pool, 6 Seepage pit, 7 Pit privy, 8 Sewage lagoon, 9 Feedyard, 10 Livestock pens, 11 Fuel storage, 12 Fertilizer storage, 13 Insecticide storage, 14 Abandoned water well, 15 Oil well/Gas well, 16 Other (specify below). Direction from well? NORTHEAST How many feet? 65

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows: 0-17 TOP SOIL CLAY, 17-27 FINE SAND, 27-31 SAND, 31-33 ROCK LIMESTONE.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/11/88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 397 This Water Well Record was completed on (mo/day/yr) 11/17/88 under the business name of CENTRAL KANSAS DRILLING by (signature) Harold R. Martin