


1) LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 MC 1/4 Section Number 21 Township Number T 13 S S Range Number R 1 EM
 County: Dickinson

Distance and direction from nearest town or city street address of well if located within city?
2 E Solomon

2) WATER WELL OWNER: Gary Hamer
 RR#, St. Address, Box #: 447 0140 Hwy Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Abilene, KS. Application Number:

3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4) DEPTH OF COMPLETED WELL: 61 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 30 ft. 2. . ft. 3. . ft.
 WELL'S STATIC WATER LEVEL: 16 ft. below land surface measured on mo/day/yr 7-18-02
 Pump test data: Well water was . ft. after . hours pumping . gpm
 Est. Yield 10-15 gpm Well water was . ft. after . hours pumping . gpm
 Bore Hole Diameter: 2 1/2 in. to 3 1/2 ft., and 7 in. to 61 ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes. X No. X; If yes, mo/day/yr sample was sub-
 mitted Water Well Disinfected? Yes X No

5) TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued. X Clamped. .
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded. .
 7 Fiberglass Threaded. .
 Blank casing diameter: 5 in. to 2 1/2 ft., Dia. 12 in. to 61 ft., Dia. . in. to . ft.
 Casing height above land surface: 12 in., weight 12.5 lbs./ft. Wall thickness or gauge No. 12/19
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) .
 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) . ft.
 SCREEN-PERFORATED INTERVALS: From 25 ft. to 40 ft., From . ft. to . ft.
 From . ft. to . ft., From . ft. to . ft.
 GRAVEL PACK INTERVALS: From 20 ft. to 61 ft., From . ft. to . ft.
 From . ft. to . ft., From . ft. to . ft.

6) GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other .
 Grout Intervals: From 0 ft. to 20 ft., From . ft. to . ft., From . ft. to . ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage .
 Direction from well? S How many feet? 75+

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	22	Clay Sandy			
22	28	fine Sand			
28	35	Med Sand			
35	61	Gray + Blue Shale			

7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-18-02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 120 This Water Well Record was completed on (mo/day/yr) 7-25-02 under the business name of Backhoe Drilling by (signature) [Signature]