WAIER W	ELL R	ECORD	Form					urces: App. No.			
1 LOCATIO	N OF W Dick	ATER WELL:	Fraction NW 1/4	SE 12 S	SW 1/4 Se	ction Nu 18	ımber	Township Nur	mber	Range Number R 1 E	
County: Dickinson NW 1/4 SE 1/2 SW 1/4 18 T 13 S R 1 E Distance and direction from nearest town or city street address of well if located within city? 302 E. 4 th St., Solomon, KS Latitude: N 38.91783°											
Longitude: W 97.36617°											
2 WATER WELL OWNER: KDHE Elevation: Pin: 1172.26 TOC:1171.95										5	
RR#, St. Ad	x # : 1000 S		Datum: above mean sea level								
City, State,	ZIP Code	: Topeka	KS 66612					lethod: legal su			
3 LOCATE V	VELL'S	4 DEPTH OF	COMPLE	TED WELL	34			ft.			
3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL 34 ft. LOCATON MW9											
		Donth (a) Craur	duratan En a	aumtanad 1		VI VV <i>3</i>	6 2		ft 2	ا ء	
WITH AN		Depth(s) Groun	idwalei Elici	ountered i		· ·	- 11. 2		11. 5	ft. ny/yr 1/30/08	
SECTION	BOX:	WELL'S STA	IIC WATER	CLEVEL	20.70 ft.	below lar	nd surfa	ce measured on	mo/da	ay/yr 1/30/08	
N		Pum	test data:	Well water v	was	ft.	after	hours p	pumpii	ng gpm	
		Est. Yield	gpm:	Well water v	was	ft.	after	hours p	pumpii	ng gpm	
l l-nw-	: 1	WELL WATE	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well								
1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify)								r (Specify below)			
SW SE 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) (10) Monitoring well										()	
										fives molder/rms	
was a chemical bacteriological sample submitted to Department. Tes 110 /k , if yes, morady yes										i yes, mo/day/yrs	
S Sample was submitted Water Well Disinfected? Yes No X											
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped											
1 Steel	3	RMP (SR) 6	A shestos-C	ement G	Other (sr	ecify bel	low)	,	Welde	1	
2 PVC	1	ABS 7	Fiberglass	omone ,	o incr (sp	cerry ou	,	-	Thread	ed V	
2) FVC	4	ADS /	ribergiass	D:			<u>-</u> -	D:-	:		
PVC 4 ABS 7 Fiberglass Threaded X Blank casing diameter 2 in. to 14 ft., Dia in. to ft., Dia in. to ft. Casing height below land surface 0.31 ft., Weight lbs./ft. Wall thickness or gauge No.											
Casing height below land surface 0.31 ft., Weight lbs./ft. Wall thickness or gauge No.											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify)											
2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
1 Continuous slot 3 Mill slot 5 Guaze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)											
2 Louvered shutter 4 Key punched o wire wrapped 8 Saw Cut 10 Other (specify)											
SCREEN-PERFORATED INTERVALS: From 14 ft. to 34 ft. From ft. to ft. From ft. to ft.											
			From		ft. to		ft. Fro	om	ft. to) tt.	
GRAVE	L PACK	INTERVALS:	From	13	ft. to	34	ft. Fro	om	ft. to) ft.	
			From		ft. to		ft. Fre	om	ft. to	ft.	
From ft. to ft. From ft. to ft. From ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other concrete, 0-2 ft.											
Crout Intervals	Enon	11. I Neat cen	12 6	Enom	S Benton	110		Eram	11.	ft to ft	
Grout Intervals From 2 ft. to 13 ft. From ft. to ft. From ft. to ft.											
What is the nearest source of possible contamination:											
1 Septic tai			nes 7 Pit pr		0 Livestoc			ecticide Storage		16 Other (specify	
2 Sewer lin		5 Cess poo		ge lagoon (l				andoned water v	well	below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/ gas well											
Direction from well? Northwest How many feet? ~100 ft.											
FROM T	O	LITHO	LOGIC LOG	7	FROM	TO	1	PLUGGING	INTE	ERVALS	
		rass, topsoil with			18	20	Clavey	silt, gray-brow			
0.5		ayey silt, very da			20	25		silt, gray-brow			
0.5		odor	ik biowii, III	ioist,	25	30		silt, gray-brow			
3		and, brown, fine,	moderately	sorted moiet		35		silt, gray-brow			
		odor	inductately s	ortea, moist	30			sand at 30 feet		, 110 0401	
8		and, brown, fine,	fairly well or	orted moist	-		Coarse	Salid at 50 lect			
0		odor	idiliy Well St	ortea, moist							
13		and, little clay, fir	e brown fo	irly well							
13		rted, nearly satur					Flushr	nount waiver f	rom R	ROW	
	30	rica, nearly satur	atea, no out	<u> </u>	+		1 143111	waiter I		· · · · · · · · · · · · · · · · · · ·	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Denstructed. (2) reconstructed. or (3) plugged											
under my jurisdiction and was completed on (mo/day/year) 1/28/08 and this record is true to the best of my knowledge and belief.											
Kansas Water W	ell Contra	ctor's License No.	757	This Wa	ter Well Rec	ord was c	omnlete	d on (mo/day/yea	r) 2	/18/08	
		f Larsen & Ass			by (signatu						
							nortman	of Health and Envi	ronman	t Bureau of Water	
INSTRUCTIONS: Please fill in blanks or circle the correct answers. Send top three copies to Kansas Department of Health and Environment. Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send-opeko WATER WELL OWNER and retain one for											
your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell.											