WATER WELL RECORD	Form W	WC-5	Div	vision of Water	r Resources App. No).		
1 LOCATION OF WATER WELL:	Fraction 45E 45E	1/4 SE 1/4	Section	on Number	Township No.	Range N	ĭE □W	
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here .		Global Positioning System (GPS) information: Latitude: 38.54.02.23 (in decimal degrees) Longitude: 9.5.14.04.21 (in decimal degrees)						
non nearest town of intersection. If at owner's auditess, effect field			Longi	Longitude: 9.5.14.04.21 (in decimal degrees)				
				Elevation:				
RR#, Street Address, Box #: 1112 A 12124 DA			Collec	Collection Method:				
City State 7ID Code			X [☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey				
3 LOCATE WELL LAWRENCE, KS				Est. Accuracy:				
WITH AN "X" IN 4 DEPTH (WITH AN "X" IN 4 DEPTH OF COMPLETED WELL は は しゅうしゅうしゅう (2) こうしゅう (3) こうしゅう (4) というしゅう (4) とい				2 "	• .	2	
SECTION BOX: Depth(s) Grown WELL'S ST	Depth(s) Groundwater Encountered (1). 15 ft. (2)							
Pt	Pump test data: Well water wasft. after hours pumping gpm							
W - NW - NE - EST. YIELD 15				ft. after hours pumping gpm				
WELL WATER TO BE USED AS: ☐ Public water supply ☐ Geothermal ☐ Injection well								
SW SE								
Was a chemical/bacteriological sample submitted to Department? Yes No								
S If yes, mo/day/yr sample was submitted 1 mile Water well disinfected? Yes No								
5 TYPE OF CASING USED: Steel Y PVC Other								
CASING JOINTS: Solution Glamped Welded Threaded Casing diameter 5.50 in. to								
Casing height above land surface. 2.4								
TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel YPVC Other (Specify)								
Brass Galvanized Steel None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)								
Louvered shutter Key punched Wire wrapped Saw cut , Other (specify) SCREEN-PERFORATED INTERVALS: From								
From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 135 ft. to 25 ft., From ft. to ft.								
GRAVEL PACK INTERVALS: From								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
Grout Intervals: From								
Septic tank						below)		
☐ Watertight sewer lines ☐ Seepa	Fuel stora Fertilizer	storage	Oil well/ga					
Promise To Direction from well NOLTAO	OGIC LOG	Distance	from we TO	ell 150.".	OG (cont.) or PLU			
0 3 DKBLA tooso		FROM	10	LITIO. D	oo (com.) or r no		TATTICALITIES	
13 13 Jullow Bin u	rathered sha	le						
13 75' Bray shale	w/coal seama	225	4 No. 10 No.		\$11 - E 12004 - PEN - F 9900 - PEN -			
87 95 Klay shale ti	sandy ohales							
95 110 Kray sandst								
115 133 BLAY DAVAS	tone							
133 135 DK Bizy Bin	Limestone-hau							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year)								
under the business name of ().	mimmuntal.		by (s	signature) .(Amas Pul	RUD.		
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include <u>fee</u> of \$5.00 for each <u>constructed</u> well. Visit us at http://www.kdheks.gov/waterwell/index.html .								
KSA 82a-1212								