## WATER WELL RECORD KSA 820-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

|  | County              | Fraction         |     | Section number |    | Township number Range number   |   |                                 |  |
|--|---------------------|------------------|-----|----------------|----|--|---|---------------------------------|--|
| 1. Location of well:   | Dickinson           | SE 1/4 NE 1/4 NW | 1/4 | 19             |    | r 13 s   | <sub>R</sub> 2  | (E)W                            |  |
| 2. Distance and direction from nearest town or city:  117 Westwood Drive  R.R. or street:                        |                     |                  |     |                | 11 | Mm. Lauxman<br>117 Westwood Drive<br>Abilene, Kansas 67410   |   |                                 |  |
| 4. Locate with "X" in section below:  Sketch map:  ADDRAINAGE  HOUSE  SET  S  S  S  S  S  S  S  S  S  S  S  S  S |                     |                  |     | E PANK         |    | 6. Bore hole dia. 8 in. Completion date  Well depth 59 ft. 3/3/76  7. X Cable tool Rotary Driven Dug Hollow rod Jetted Bored Reverse rotary  8. Use: Domestic Public supply Industry X Irrigation Air conditioning Stock Lawn Oil field water Other  9. Casing: Material DIST Height: Above or fellow Threoded Welded B Surface 18 in.  RMP PVC Weight Ibs./ft.    |   |                                 |  |
| 1 → 1 Mile → 1  5. Type and color of material  |                     |                  |     | From           | То | Dia 5 in. to 59 ft. depth Wall Thickness: inches or Dia in. to ft. depth gage No. 0.258  |   |                                 |  |
| Sand   |                     |                  |     | 0              | 4  | 10. Screen: Manufacturer's name  Western Plastics  Type PVC Dia5"  |   |                                 |  |
| Limestone rock   |                     |                  |     | 4              | 12 | Slot/gauze 3/32 Length 20! Set between 39 ft. and 59 ft.   |   |                                 |  |
| Yellow clay  |                     |                  |     | 12             | 24 | ft. andft.<br>Gravel pack? Yes_ Size range of material 1/16to 3/3  |   |                                 |  |
| Red clay   |                     |                  |     | 24             | 43 | 11. Static water level: mo./day/yr. 39 ft. below lond surface Date 3/3/76  |   |                                 |  |
| Limerock   |                     |                  |     | 43             | 55 | 12. Pumping level below land surfaces: ft. after hrs. pumping g.p.m.   |   |                                 |  |
| Ha   | rd light gray shale |                  |     | 55             | 59 | ft. after  Estimated maximum yield  13. Water sample submitted: Yes X No  14. Well head completion: Pitless adapter  15. Well grouted? Yes With: X Neat cement Depth: From O ft. to  16. Nearest source of possibleft.  16. Nearest source of possibleft.  Well disinfected upon completations  Well disinfected upon completations  17. Pump: Manufacturer's name | mode above  Bentonite 10 ft. e contamination: Se ast Type Lation? Yes Not installed HP Vo ft. capacity Turbin | grode  Concrete  DtlC  nk  X No |  |
| 18. Elevation: 1160  Topography: Hill Slope Upland Valley  | 19. Remarks:        | nor il lieuwy    |     |                |    | 20. Water well contractor's of This well was drilled under m is true to the best of my know Rader Drilling   | certification: y jurisdiction and this eledge and belief. Z Co. 1 Kansas 674                                  | — °                             |  |