

1 LOCATION OF WATER WELL: Fraction NW 1/4 NE 1/4 NW 1/4 Section Number 21 Township Number T 13 S Range Number R 2 E

County: Dickinson Distance and direction from nearest town or city street address of well if located within city? 3 blocks west of 15 Hwy on west 1st in Abilene, Ks.

2 WATER WELL OWNER: Gail Rodda RR#, St. Address, Box #: 315 W 1st City, State, ZIP Code: Abilene, Kansas 67410 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram of a 2x2 section box with NW, NE, SW, SE quadrants and an 'X' in the NW quadrant]

4 DEPTH OF COMPLETED WELL: 59 ft. ELEVATION: 49 ft. Depth(s) Groundwater Encountered: 1. 49 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL: 16 ft. below land surface measured on mo/day/yr 5/6/88. Pump test data: Well water was ft. after hours pumping gpm. Est. Yield: 23 gpm. Well water was ft. after hours pumping gpm. Bore Hole Diameter: 9 in. to 59 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded. Blank casing diameter: 5 in. to 59 ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface: 14 in. weight: 160 lbs./ft. Wall thickness or gauge No. 214. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 49 ft. to 59 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 24 ft. to 59 ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? NORTHWEST How many feet? 65

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	15	DARK CLAY			
15	35	BROWN CLAY			
35	40	BLUE CLAY			
40	46	SAND & BLUE CLAY			
46	55	SAND			
55	56	LIMESTONE			
56	58	TOURQUOIS SHALE			
58	59	RED SHALE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/6/88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 397 This Water Well Record was completed on (mo/day/yr) 5/12/88 under the business name of CENTRAL KANSAS DRILLING by (signature) Harold D. Martin

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.

10-8700000232