			ATER WELL REC	ORD Form V	WC 5	KSA 82a-	1212 ID No				
1 LOCAT	ION OF WA	TER WELL:	Fraction	OND FOIIII V	VVVC-5		tion Number	Township Numbe	r	Range Nur	nber
	ickins			S77 1/4	J.J. 1/4		17		s	R 2	E₩₩
Distance a	nd direction	from nearest to	wn or city street	address of well if	located wit	hin city?	1 1				
From 2 WATER	Hwy 1 RWELLOW	5 & 1st NER: Lynn	St. in A	bilene, K	(s go	West	on West	$1st1\frac{1}{2}$ miles		wy 40 8 e North	
_	ddress, Box	# : 1001	N. VanBı ene, Kans					Board of Agricult Application Num	ure, Divisi		
		CATION WITH	4 DEPTH OF C	COMPLETED WE	LL7	7	ft. ELEVA	TION:			
	N SECTION		Depth(s) Groun	ndwater Encounte	ered 1	5	2ft.	2e measured on mo/day	ft <u>.</u> ,3,		ft.
	N	I	WELL'S STATI	C WATER LEVEL	4.1	ft. beld	w land surfac	e measured on mo/day/ afterho	yr .//	/	žanr
	1	1						after h			
- ·	-NW	- NE	WELL WATER	TO BE USED AS	6: 5 Pul	olic water s	supply	8 Air conditioning	11 Inject	on well	
,,,		; _	1 Domestic	, , , , , , , , , , , , , , , , , , , ,							w)
	1	- 	2 Irrigation	4 industrial	7 001	nestic (lav	vii & garden)	—— wioriitoring weii			
	-sw -	- SE) M/a = = = b = == '= :	-1/14111			D = = = = = = = = = = = 10 \	/aa Na W . 16			waa aul
	-300 -	1	was a chemica	al/bacteriological	sample sur	mittea to	Department? \ Wa	/es; If ater Well Disinfected? Y	yes, mo/aa es *	ay/yrs sample No	
		1					•••				
5 TYPE (S S ANK (CASING USED:		5 Wrought iron	<u> </u>	8 Concre	ate tile	CASING JOINTS	Glued	* Clamper	1
1 Stee		3 RMP (S		6 Asbestos-Ce			specify below			Olampo	
2 PVC		4 ABS	,	7 Fiberglass				•		t	
Blank casir	ng diameter	5	in. to	7.7 ft.	, Dia		in. to	ft., Dia		in. to	f
_	-			in., weight	***************************************			lbs./ft. Wall thickness o		o•	
		R PERFORATION 3 Stainles	ON MATERIAL:	5 Fiberglass		7 PV	C IP (SR)	10 Asbesto			
1 Stee 2 Bras		4 Galvani		6 Concrete tile	+	9 AB		12 None us			
		RATION OPENI	NGS ARE:		5 Guazed	wrapped		8 Saw cut	11	None (open	hole)
	tinuous slot		Mill slot		6 Wire wra			9 Drilled holes		` '	,
	ered shutte		Key punched		7 Torch cu	ıt		10 Other (specify)		•••••	f
SCREEN-F	PERFORATI	ED INTERVALS	6: From	4.7f	t. to	.7.7	ft., From		. ft. to		f
,		OK INTERVAL									
,	SHAVEL PAI	CK INTERVALS									
	T MATERIA		at cement	2 Cement gr				1 Other			
				ام ft., From		ft. t		ft., From			
			contamination:	7 [Dit meion.		10 Livest	•		doned water	well
1 Septic tank 4 Lateral lines 2 Sewer lines 5 Cess pool					7 Pit privy 8 Sewage lag		11 Fuel s	zer storage		Oil well/Gas well Other (specify below)	
3 Watertight sewer lines 6 Seepage pit					9 Feedyard						•
Direction fr		WEST	pago pit	APPROX	-		How man	-			
FROM	то		LITHOLOGIC			FROM	ТО		NG INTER	RVALS	
0	16	BROWN	SOFT SAN	DY CLAY							
16	18			AVEL MIXE	ED						
18	20	ŀ	COLOR LIM								
20	21			LE & CLAY	Z						
21	30		SHALE & C								
30	33		GRAY LIME	STONE							
33	39	GRAY C									
39	50		IALE & CL	AY							
50	52	GRAY S									
52	56		RAY CLAY								
56	68 77	1	COLOR LIM								
<u> 68</u>		GRAY 1	LIMESTONE								
7 CONTR	ACTOR'S C	B L ANDOWNI	ER'S CERTIFICA	TION: This water	r well was	(1) constr	icted (2) reco	onstructed, or (3) plugge	ed under r	ny jurisdiction	and wa
								cord is true to the best of			
Water Well	Contractor's	Licence No	397	Thi	s Water W	ell Record	was complete	d on (mo/day/yr) .7/ signature)	26/	0,4	
under the b	usiness nam	ne of CENTE	RAL KANSA	S DRILLIN	٧G		by (signature)	Wma	rtin	