


1 LOCATION OF WATER WELL: Fraction SE 1/4 NE 1/4 SE 1/4 Section Number 16 Township Number T 13 S Range Number R 2 E  
 County: Dickinson

Distance and direction from nearest town or city street address of well if located within city?  
In Abilene, Ks go West on 1st St. to Hwy 40 & 1/4 mile North to 4th St & West to  
 2 WATER WELL OWNER: Gene Preim 302 - Tower Ave  
 RR#, St. Address, Box # : 808 NW 7th Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code : Abilene, Kansas 67410 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 4 DEPTH OF COMPLETED WELL 10.1 ft. ELEVATION:  
 Depth(s) Groundwater Encountered 1 6.3 ft. 2 7.3 ft. 3 14.0 ft.  
 WELL'S STATIC WATER LEVEL 5.1 ft. below land surface measured on mo/day/yr 7 / 14 / 04  
 Pump test data: Well water was \_\_\_\_\_ ft. after \_\_\_\_\_ hours pumping \_\_\_\_\_ gpr  
 Est. Yield 8-10 gpm: Well water was \_\_\_\_\_ ft. after \_\_\_\_\_ hours pumping \_\_\_\_\_ gpr  
 WELL WATER TO BE USED AS:  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes \_\_\_\_\_ No \*; if yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes \* No

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued \* Clamped \_\_\_\_\_  
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded \_\_\_\_\_  
 7 Fiberglass Threaded \_\_\_\_\_  
 Blank casing diameter 5 in. to 10.1 ft., Dia \_\_\_\_\_ in. to \_\_\_\_\_ ft., Dia \_\_\_\_\_ in. to \_\_\_\_\_ ft.  
 Casing height above land surface 1.4 in., weight 200 lbs./ft. Wall thickness or gauge No. 25.0  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement  
 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify) \_\_\_\_\_  
 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify) \_\_\_\_\_ ft.  
 SCREEN-PERFORATED INTERVALS: From 5.1 ft. to 10.1 ft., From \_\_\_\_\_ ft. to \_\_\_\_\_ ft.  
 GRAVEL PACK INTERVALS: From 2.4 ft. to 10.1 ft., From \_\_\_\_\_ ft. to \_\_\_\_\_ ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other \_\_\_\_\_  
 Grout Intervals: From 3 ft. to 2.4 ft., From \_\_\_\_\_ ft. to \_\_\_\_\_ ft., From \_\_\_\_\_ ft. to \_\_\_\_\_ ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage \_\_\_\_\_  
 Direction from well? NORTH How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	*PLUGGING INTERVALS*
0	4	DARK SANDY CLAY	79	89	GRAY SHALE
4	19	BROWN SANDY CLAY	89	94	HARD GRAY LIMESTONE
19	20	LITE COLOR LIMESTONE	94	101	GRAY SHALE
20	23	TAN CLAY			
23	32	GRAY CLAY			
32	35	LITE COLOR SHALE & CLAY			
35	36	LIMESTONE			
36	39	LITE COLOR SHALE & CLAY			
39	52	RED SHALE & CLAY			
52	58	GRAY CLAY & SHALE			
58	62	LIMESTONE			
62	66	LITE COLOR CLAY & SHALE			
66	69	LITE COLOR LIMESTONE			
69	79	GRAY LIMESTONE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7 / 14 / 04 and this record is true to the best of my knowledge and belief. Kansas  
 Water Well Contractor's Licence No 397 This Water Well Record was completed on (mo/day/yr) 7 / 15 / 04  
 under the business name of CENTRAL KANSAS DRILLING by (signature) Sheldon D. Martin