


1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 SW 1/4 Section Number 4 Township Number T 13 S Range Number R 2 E/W*
 County: Dickinson

Distance and direction from nearest town or city street address of well if located within city?
North of Abilene, Ks on Hwy 15 to 2400 Ave & go 1/2 mile West North side

2 WATER WELL OWNER: Tim Schenck
 RR#, St. Address, Box # : 1915 Hwy 15 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Abilene, Kansas 67410 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  DEPTH OF COMPLETED WELL 8.5 ft. ELEVATION: ft.
 Depth(s) Groundwater Encountered 1 6.1 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 5.1 ft. below land surface measured on mo/day/yr 8 / 9 / 05
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 1.0 gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No *; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes * No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued * Clamped
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
 2 PVC 4 ABS 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 8.5 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 1.3 in., weight 2.00 lbs./ft. Wall thickness or gauge No. 2.50
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-Cement
 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify)
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 6.7 ft. to 8.5 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 2.3 ft. to 8.5 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 2 ft. to 2.3 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? NORTHEAST APPROX How many feet? 120

FROM	TO	LITHOLOGIC LOG	FROM	TO	* PLUGGING INTERVALS *
0	4	BROWN CLAY	66	71	LITE COLOR SHALE & LIMESTONE
4	11	LITE COLOR SHALE & CLAY	71	85	DARK HARD LIMESTONE
11	18	MAROON CLAY & SHALE			
18	23	LITE COLOR SHALE			
23	24	SOFT LIMESTONE			
24	26	LITE COLOR SHALE			
26	27	LITE COLOR LIMESTONE			
27	30	LITE COLOR SHALE			
30	33	LITE COLOR LIMESTONE			
33	42	GRAY SHALE			
42	43	GRAY LIMESTONE			
43	50	GRAY SHALE			
50	61	RED SHALE & CLAY			
61	66	LITE COLOR CLAY & LITE GRAY			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8 / 9 / 05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 397 This Water Well Record was completed on (mo/day/yr) 8 / 12 / 05 under the business name of CENTRAL KANSAS DRILLING by (signature) Harold B. Martin