

| | | | | |
|---------------------------|-----------------------------|----------------|-----------------|------------------|
| 1 LOCATION OF WATER WELL: | Fraction | Section Number | Township Number | Range Number |
| County: <u>Dickinson</u> | <u>NE 1/4 NW 1/4 SW 1/4</u> | <u>9</u> | <u>T 13 S</u> | <u>R 2 E 1/4</u> |

Distance and direction from nearest town or city street address of well if located within city?
Located at 1505 Park Place, Abilene, Kansas

2 WATER WELL OWNER: Carl Hansen

RR#, St. Address, Box # : 1505 Park Place Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Abilene, Kansas 67410 Application Number: _____

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL 6.0 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1 3.4 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 3.0 ft. below land surface measured on mo/day/yr 9 / 14 / 05
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 2.0 gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well
 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
7 Domestic (lawn & garden) 10 Monitoring well

N

| | | | |
|--------|--------|--------|--------|
| | | | |
| - NW - | - NE - | - SE - | - SW - |
| | | | |
| W | * | E | S |

Was a chemical/bacteriological sample submitted to Department? Yes No * ; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes * No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued * Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded

Blank casing diameter 5 in. to 6.0 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 2.0 in., weight 2.00 lbs./ft. Wall thickness or gauge No. 2.50
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) ft.

SCREEN-PERFORATED INTERVALS: From 3.0 ft. to 6.0 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 2.3 ft. to 6.0 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 2.3 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage

Direction from well? WEST APPROX How many feet? 10

| FROM | TO | LITHOLOGIC LOG | FROM | TO | PLUGGING INTERVALS |
|------|----|---------------------------|------|----|--------------------|
| 0 | 2 | DARK CLAY TOP SOIL | | | |
| 2 | 18 | BROWN CLAY | | | |
| 18 | 31 | MAROON & RED CLAY & SHALE | | | |
| 31 | 33 | GRAY SHALE | | | |
| 33 | 35 | LITE COLOR LIMESTONE | | | |
| 35 | 47 | GRAY SHALE | | | |
| 47 | 53 | DARK LIMESTONE | | | |
| 53 | 60 | GRAY SHALE | | | |

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9 / 14 / 05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 397 This Water Well Record was completed on (mo/day/yr) 9 / 20 / 05 under the business name of CENTRAL KANSAS DRILLING by (signature) Harold D. Martin