			1000								
	N OF WATE		Fraction	or	A		ion Number		1	Range Nu	~
ounty:	Dick		SW ½				16	т 13	S	R 2	(E)W
istance and	direction fro	m nearest tow	n or city street ad	dress of well it	located wit	hin city?					
			2 nd St., Abiler							 	
			Rice Collingw	100a							
RR#, St. Add	iress, Box#	: 36 Stra	tford Rd					Board of Agricul	ture, Divis	ion of Water R	esources
City, State, Z	IP Code	: Wichit	a, Ks 67206					Application Num	ber:		
LOCATE	WELL'S LOC	ATON WITH	4			20			44	E2 E4	
AN "X" IN	SECTION	OX:	UEPIHOF C			30.3	n. ELE	ATION:	17	93.91	
	N		Depth(s) Ground				ft	2	ft. 3	}	ft.
1		!	WELL'S STATIC	WATER LEV	EL 20).4 ft.	below land s	urface measured on	mo/day/y	r	
		NE	Pump	test data: V	Vell water w	as	f	t. after	hours pu	mping	gpm
	- 1400		Est. Yield					t. after			
₿wL		E				30.	5	ft. and	in	to	ft.
- "			WELL WATER T	O BE USED A	S: 5 Put	lic water su	pply	ft. and 8 Air conditions 9 Dewatering	ng 11	Injection well	
l L.	_ s.v l	- 65	1 Domestic	3 Feed lot	6 Oil	field water s	supply	9 Dewatering	12	Other (Specif	y below)
	Sw	- SE	2 Irrigation	4 Industria	7 Lav	m and gard	len (domesti	c) 10 Monitoring v	veli		
l L	_ x							Yes No X			
	_ ^ _s		submitted					ter Well Disinfected			
E TYPE OF	COLANIA CAG	SING USED:		£ 186	l-nn	9 Conor					
				5 Wrought			ete tile				
1 Stee		3 RMP	SR)	6 Asbesto		9 Other	(specify belo	W)	Weide	ded)	;
2 PVC		4 ABS		7 Fibergla					Threa	ded	·
Blank casing	diameter	2	in. to 15	ft., Dia		in. t	0	ft., Dia Wall thickness or ga		in. to	ft.
asing heigh	nt above land	surface	0	in., weight	.7	116	lbs./ft.	Wall thickness or ga	auge No.	.154	4
YPE OF SC	CREEN OR P	ERFORATION	N MATERIAL:			7	PVC	10 Asbes	los-cemen	rt	
1 Stee	eł	3 Stainle	ess steel	5 Fibergla	88	8	RMP (SR)	11 Other	(specify)		
2 Bras	58	4 Galvar	nized steel	6 Concrete	e tile	9	ABS	12 None (8 Saw cut	used (oper	n hole)	
CREEN OF	R PERFORA	TION OPENIN	GS ARE:		5 Gauzeo	wrapped		8 Saw cut	1	11 None (ope	n hole)
1 Con	ntinuous slot	3	Mill slot		6 Wire wr			9 Drilled holes			
2 Lour	vered shutter	4	Key punched		7 Torch o	ut		10 Other (specify)		
CREEN-PE	ERFORATED	INTERVALS:	From	15 ft	to	30	ft. F	rom	ft. to		ft.
			From					rom			
GRA	VEL PACK I	NTERVALS:		13 #	to	30	ft. F	rom	ft. to		ft.
0.0			From		to			rom			
e lanauri		4 11			101	100	4	4 Other	11. 10)	I La
JGROUT	MATERIAL:	1 Neat C	pement 2	Cement grou		3 Ben	tonite	4 Other			
				ft. From		1t. t		ft. From			
		e of possible o	contamination:					tock pens		ndoned water	well
1 Sep	otic tank		4 Lateral lines		Pit privy		11 Fuel:			vell/ Gas well	
2 Sev	ver lines		5 Cess pool		Sewage la	goon		zer storage		er (specify belo	
3 Wat	tertight sewer	lines	6 Seepage pit	9	Feedyard		13 Insec	ticide storage	CONT	AMINATE	USITE
Direction from							How many			military and the second	
FROM	TÖ	CODE		OGIC LOG		FROM	TO	PLUC	GING IN	TERVALS	
0	.5		avel/grass				ļ		······································		
.5	1		ndy cilty cla				ļ				
1	6		t, tr. Clay & s								
6	13		yey silt, mo	st							
13	20		t, tr. clay	· · · · · · · · · · · · · · · · · · ·							
20	28		t, tr. Clay								
20 1	30.5	Sil	t tr. clay								
28											
28								TATALON TO A STATE OF THE STATE			
28											
28											
28											
28											
28											
28											
	ACTOR'S OR	LANDOWNEI	R'S CERTIFICATI	ON: This water	er well was (1) construc	ted, (2) recor	estructed, or (3) plugg	jed under	my jurisdiction	and was
7]CONTRA				ON: This water	er well was (
7 CONTRA	n (mo/day/yr)	10-04-20	05		er well was (and th	is record is t	rue to the best of my	knowledg	e and belief. I	Cansas
7 CONTRA	n (mo/day/yr)	10-04-20 icense No.	05	ON: This wate		and th	is record is to Vater Well Re		knowledg i on (mo/d	ge and belief. I	