WATEI	R WELL	RECORD	For	m WWC	-5	ivision of Wat	er Reso	urces: App. No.		
1 LOCA	TION OF	WATER WELL: ckinson	Fraction SE !	SE 14	SW 34	Section Nu	mber	Township Number	Range Number	
Distance a	and direction	n from nearest town	or city stre	eet address	of well if	Global Posit	tioning	T 13 s System (decimal degr	ees. min. of 4 digits)	
located within city? 1407 NW 3 rd , Abilene, KS Latitude: N 38.93022° Longitude: W 97.21469°										
	OWNER: Green's		Elevation: RIM: 1201.51; TOC: 1201.16							
RR#, S	St. Address.	Box # : PO Box	189	0		Datum:	above	e mean sea level		
City. State, ZIP Code : Abilene, KS 67410 Data Collection Method: legal survey 3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL 20 ft										
LOCATON MW15										
	I AN "X" I	N Depth(s) Grour	idwater En	countered l			ft. 2	ft. 3	ft.	
SECT	SECTION BOX: WELL'S STATIC WATER LEVEL 18.63 ft. below land surface measured on mo/day/yr 12/28/09									
	N	Pump	test data:	Well water	er was	ft. a	ıfter	hours pumpi	ng gpm	
Est. Yield gpm: Well water was ft. after hours pumping gpm										
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)										
W E Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well										
- sw sE 2 inigation 4 industrial 7 Boilestic (lawn & garden) (sylviolitoring wen										
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs										
	S	Sample was sul	omitted			W	ater W	ell Disinfected? Yes	No X	
5 TYPE	OF CASI	NG USED: 5	Wrought	Iron	8 Conc	rete tile	CASI	NG JOINTS: Glued	Clamped	
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded										
2 PVC 4 ABS 7 Fiberglass Threaded X Blank casing diameter 2 in. to 10 ft., Dia in. to ft., Dia in. to ft. Casing height below land surface 0.35 ft., Weight lbs./ft. Wall thickness or gauge No.										
Blank casing diameter 2 in. to 10 ft., Dia in. to ft., Dia in. to ft.										
Casing height below land surface 0.35 ft., Weight lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL:										
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)										
2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:										
1 Continuous slot (3) Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)										
1 Continuous slot (3) Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 10 ft. to 20 ft. From ft. to ft.										
SCREEN-PERFORATED INTERVALS: From 10 ft. to 20 ft. From ft. to ft.										
From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 8 ft. to 20 ft. From ft. to ft.										
From ft. to ft. From ft. to ft.										
6 CDOUT MATERIAL: 1 Next cement 2 Cement grout 3 Pentonite (A)Other Congress 0.36										
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete: 0-2ft Grout Intervals From 2 ft. to 8 ft. From ft. to ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination:										
What is the nearest source of possible contamination:										
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify)										
2 Sewer lines 5 Cess pool 8 Sewage lagoon (1) Fuel storage 14 Abandoned water well below)										
3 Watertight sewer lines 6 Seepage pit 9 Feedyard Direction from well? SE 12 Fertilizer storage 15 Oil well/ gas well How many feet? ~120 ft										
FROM	ТО		LOGIC LO)G	FRC			PLUGGING INTE	PVAIS	
0	1	Asphalt	LOGIC L	<i></i>	TRC	171		LUGGING INTE	AC VALS	
1	4	Red brown silty clay, n								
4	9	Red brown silty clay with fine to coarse sand, mod.								
9	11	Red brown fine to coar	se sand, trac	e clav						
11	20	Red brown with black			d					
20		Limestone		***************************************						
1		77.					Flushm	ount waiver from B	ow	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed. (2) reconstructed. or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/8/09 and this record is true to the best of my knowledge and belief.										
Kansas Wa	urisdiction ai iter Well Cor	id was completed on (itractor's License No	mo/day/yea 757			and this re	ecord is mpleted	on (mo/day/year) 12	nowledge and belief.	
		of Larsen & Asso				ature)	-	Quiteren		
INSTRUCTIONS: Please fill in blanks or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water.										
Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell.										