WATER WELL RECORD Form WWC-5	Division of Water Resources App. No.
1 LOCATION OF WATER WELL: Fraction	Section Number Township No. Range Number T 15 8 R 2 WE W
Street/Rural Address of Well Location: if unknown, distance & direction	Global Fositioning System (GPS) information:
from nearest town or intersection: If at owner's address, check here .	Latitude: (in decimal degrees)
from nearest town or intersection: If at owner's address, check here From Abiliar to North & Mill of 15 Huy	Longitude: (in decimal degrees)
211110 2 174 6 500 4 70	Elevation:
To 2440 Road Thin Go East & Mile	<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, ☐ NAD 27
2 WATER WELL OWNER: Mrs. Lottie Touksly	Collection Method:
2 WATER WELL OWNER: Ars. Lottie Tinksly RR#, Street Address, Box #: 2440 Hoven Drive	GPS unit (Make/Model:)
City, State, ZIP Code : Philipse, ky 67416	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m
A K O CLY MAKE A KANDER A	
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL	2.0 / ft.
SECTION BOX: Depth(s) Groundwater Encountered (1)7.6	ft. (2) ft. (3) ft.
SECTION BOX: Depth(s) Groundwater Encountered (1)	
Pump test data: Well water was	ft. after hours pumping gpm
EST. YIELD. 20gpm., Well water was	ft. after hours pumping gpm .ft., andin. toft.
W Bore Hole Diameter 9in. toin. to	.ft., andin. toft.
	ater supply Geothermal Injection well
	nter supply
	awn & garden
Was a chemical/bacteriological sample submitted	
If yes, mo/day/yr sample was submitted	
Water well disinfected? Yes No	
5 TYPE OF CASING USED: Steel PVC Other	
CASING JOINTS: Glued Clamped Welded Thread	ed '
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter in. to	
Casing height above land surface in., Weight Scale Wlbs./ft., Wall thickness or gauge No	
TYPE OF SCREEN OR PERFORATION MATERIAL:	
Steel Stainless Steel	Other (Specify)
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)	
SCREEN OR PERFORATION OPENINGS ABE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole) Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From 1.0.0 ft. to 1.2.0 ft., From ft. to ft.	
Lowered shutter	
SCREEN-PERFORATED INTERVALS: From 100 ft to 120 ft From ft to 120	
From Aft. to	
From	
From ft. to ft., From ft. to ft.	
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other	
Grout Intervals: From	
What is the nearest source of possible contamination:	· · · · · · · · · · · · · · · · · · ·
Septic tank Lateral lines Pit privy Livestoc	
Sewer lines Cesspool Sewage lagoon Fuel stor	
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer	
	the from well
FROM TO LITHOLOGIC LOG FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS
0, 1, Top 50, L	
1/2 Brown Clay	
12 23 YELLOW CLAY	
23 70 Brown Shall	
70 76 Limistane (MATA)	
76 86 Bry D.Ly Shole	
86 108 Brown Shall	1
108 120 Lings Tone	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This was under my jurisdiction and was completed on (mo/day/year)	ater well was constructed, reconstructed, or plugged
under my jurisdiction and was completed on (mo/day/year) D. f f	and this record is true to the best of my knowledge and belief.
Kansas Water Well Contractor's License No 4 This Water Well	Record was completed on (mo/day/year).
under the business name of Aldania. M. Drilly	by (signature) Less CMPP
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>RINT</u> (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Go	clearly. Please this in branks and check the confect answers. Send three copies cology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for	r your records. Include fee of \$5.00 for each constructed well. Visit us at
http://www.kdheks.gov/waterwell/index.html.	
KSA 82a-1212	