WATER WELL R		ı WWC-5		sion of Water	1	
Original Record		nge in Well Use		irces App. No.		Well ID
1 LOCATION OF W		Fraction (kgs)		ion Number	Township Numb	er Range Number
						R 2 ☑ E ₩
2 WELL OWNER: L	ast Name:	First				(if unknown, distance and
2	derknecht	Mark	direction from n	earest town or in	ntersection): If at owner	's address, check here:
Address: 2112 W 1st St 2112 W 1st St						
City: Abile	5 ZIP:67401	Abilene, Ks				
3 LOCATE WELL						
WITH "X" IN 4 DEPTH OF COMPLETED WELL:						
SECTION BOX:	DN BOX: Depth(s) Groundwater Encountered: 1)					
N	2) ft.	3) ft., or 4)	Dry Well			I □ NAD 83 □ NAD 27
	WELL'S STATIC WATER LEVEL:24					
		ace, measured on (mo-da		'P □ GPS		
NW NE	Pump test data: Wel	Il water was 40	ter was			
w E						
~ ' ' ~		ll water was				
SW SE	after ho	urs pumping	gpm	(Floresti		
*	Estimated Yield:	2.0.±.gpm				☐ Ground Level ☐ TOC
S		:9 in. to7.2				GPS Topographic Map
mile		in. to	π.			
7 WELL WATER TO		W. (C		10 🗖 033	C' 11 W C 1 1	
1. Domestic:		Water Supply: well ID.			ole: well ID	ease
☐ Household ☐ Lawn & Garden		ering: how many wells? Recharge: well ID			ed Uncased 0	
Livestock		ring: well ID			rmal: how many bores	
2. Irrigation		ental Remediation: well			sed Loop Horizont	
B. ☐ Feedlot	☐ Air Spa					scharge Inj. of Water
I. Industrial	☐ Recove					
Was a chemical/hacter	riological sample sul	bmitted to KDHE?	TYes ★ No	If yes, date s	sample was submitte	d:
Water well disinfected?				11) 02, 1400 1	ounipro muo ou o initio	
		PVC Other	CASIN	G JOINTS:	□ Glued □ Clamped	□ Welded □ Threaded
Casing diameter						
Casing height above land	surface 15	in. Weight20	00 lbs./ft.	Wall thickne	ess or gauge No 2.	5.0
TYPE OF SCREEN OR PERFORATION MATERIAL:						
☐ Steel ☐ Stainless Steel ☐ Fiberglass ★ PVC ☐ Other (Specify)						
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
☐ Continuous Slot ☐ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)						
□ Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole)						
SCREEN-PERFORATED INTERVALS: From						
GRAVEL PACK INTERVALS: From38 ft. to72 ft., From ft. to ft., From ft. to ft.						
GROUT MATERIA	Neat cement	☐ Cement grout 💹	Bentonite 🔲 O	ther	Δ	
Grout Intervals: From						
Nearest source of possible	ie contamination: Lateral L	ines		Livestock Pens	s □ Insecti	cide Storage
☐ Septic Tank 【图 Sewer Lines	☐ Cess Poo			Fuel Storage		oned Water Well
☐ Watertight Sewer Lin		_		Fertilizer Stora		Il/Gas Well
Other (Specify) Direction from well?	EAST AP	PROX Distance from	well?1.1.0			
10 FROM TO	LITHOL	OGIC LOG	FROM	TO L	LITHO. LOG (cont.) or	PLUGGING INTERVALS
0 7	LITE BROWN		59	7 â	LITE COLOR	LIMESTONE
7 15	LITE COLOR	SAND & LITE	GRAY CL	AY		
15 22	BROWN SAND	& CLAY	8 0	72	LITE GRAY I	IMESTONE
22 24	HARD ROCK					
24 34	GRAY TOUGH	CLAY				
34 37	HARD GRAY	LIMESTONE				
37 43	GRAY SHALE		Notes:			
43 56	BROWN SHAL	Ē				
56 59	LITE COLOR	SOFT CLAY				
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 🖈 constructed, or plugged under my jurisdiction and was completed on (mo-day-year) / 2.7 / 1.8						
under my jurisdiction a	nd was completed on	(mo-day-year)./.2.7	/.1.8 and	this record is	true to the best of m	y knowledge and belief.
Kansas Water Well Con	ntractor's License No	3.9.7 This V	Water Well Rec	ord was coppay	pleted on (mo-day-y	ear) / / 5 / 18
under the business nam	e ofCENTRAL	KANSAS DRIL	HTMGSi	gnature	cioral, m	CIVITO 6
Mail 1 white copy ale	ong with a fee of \$5.00 for	each constructed well to: I	Kansas Department	of Health and E	nvironment, Bureau of W	ater, GWTS Section,
		sas 66612-1367. Mail one			e for your records. Teleph	
Visit us at http://www.kdheks	s.gov/waterwell/index.htm	I	KSA 82a-12	14		Revised 7/10/2015