WATER WELL RECORD	Form W	WC-5	Di	ivision of Wate	er Resources App. No).	
1 LOCATION OF WATER WELL:	Fraction		Secti	on Number	Township No.	Range Number	
County: Douglas	N7/22 1/2E	14 VE 1	4 9	<u>ي ع د د</u>		R 2	
Street/Rural Address of Well Location; from nearest town or intersection: If at					g System (GPS) in		
nom nearest town or intersection. If at owner 5 activess, eneck note [2].				Latitude: (in decimal degrees) Longitude: (in decimal degrees)			
			Eleva	Elevation:			
2 WATER WELL OWNER: Steve Sellmeyer				<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, ☐ NAD 27 <u>Collection Method</u> :			
RR#, Street Address, Box #: 1582 N. 1060 Rd				GPS unit (Make/Model:)			
City, State, ZIP Code : Lawrence, KS 66046				☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m			
3 LOCATE WELL	Phocal	076					
WITH AN "X" IN 4 DEPTH OF	flugged WEL	L 20	0	ft.	4-300 bor	દડ	
	Depth(s) Groundwater Encountered (1)./23:138 ft. (2) ft. (3) ft.						
N WELL'S STAT	WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr\$						
	EST VIELD Comm. Well water was A often house numerica						
W E Bore Hole Diameter							
WELL WATER TO BE USED AS: Public water supply Domestic Feedlot Oil field water supply Dewatering Other (Specify below)							
SW SE							
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well Classed							
S If yes, mo/day/yr sample was submitted							
1 mile Water well disinfected? Yes No							
5 TYPE OF CASING USED: Steel PVC Steel OtherH. DPolye.thylco.e.							
CASING JOINTS: Glued Clamped Welded Threaded Fustor '							
Casing diameter 3/4 in. to 200 ft., Diameter in. to ft., Diameter in. to ft., Diameter in. to ft. Casing height affect and surface 36 in., Weight 50811 lbs./ft., Wall thickness or gauge No. 160. 151							
TYPE OF SCREEN OR PERFORATION MATERIAL: V							
Steel Stainless Steel PVC Other (Specify)							
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: None							
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)							
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)							
SCREEN-PERFORATED INTERVALS: From							
GRAVEL PACK INTERVALS: From							
From							
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other							
Grout Intervals: From 200 ft. to ft., From ft. ft. to ft., From ft. ft. to ft. what is the nearest source of possible contamination:							
	ines Pit privy	Livestock	pens	☐ Insecticide		er (specify below)	
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well							
Direction from well	pit recuyard		storage e from w	, <u> </u>	4		
FROM TO LITHOLOG	·	FROM	TO			GGING INTERVALS	
0 19 Sandstone							
19 123 Shale	<u> </u>						
123 138 lime - 124-							
145 150 line		200	.3	4-200'	Bores plus	nged with	
150 164 Shale				High		entonite	
164 173 lime				J			
173 189 Shale							
189 200 lime							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, ☐ reconstructed, or ☒ plugged							
under my jurisdiction and was completed on (mo/day/year) 5							
Kansas Water Well Contractor's License No. 5.6.1 This Water Well Record was completed on (mo/day/year) S.T.Y							
under the business name of business name							
(white, blue, pink) to Kansas Department of Healt	h and Environment, Bureau	of Water, Geo	logy Secti	on, 1000 SW Ja	ckson St., Suite 420,	Fopeka, Kansas 66612-1367.	
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.							
KSA 82a-1212							