WATER WELL RECORD	Form W	WC-5	Di	vision of Water	r Resources App. N	0.	
1 LOCATION OF WATER WELL County: Day 1 % 5	NE45L)45E		Section		Township No.	Range Number R 2	
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here							
1735 N. 1062 Rd. LAWrence, Ks.				Longitude: (in decimal degrees) Elevation: NAD 83, NAD 27			
2 WATER WELL OWNER: KT RR#, Street Address, Box #:	Collec	ction Method:	•				
RR#, Street Address, Box #: 925 W 28 Terr City, State, ZIP Code: 425 W Lawrey K5. Lb046				☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m			
WITH AN "X" IN 4 DEPTH SECTION BOX: Depth(s) Gr	OF COMPLETED WEL	L	78 A	tt.) ا	3) A	
SECTION BOX: Depth(s) Groundwater Encountered (1) 13 - 14.8 ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL. 26 ft. below land surface measured on mo/day/yr 8 - 2 5 ft. (2)							
P	'ump test data: Well wate	r was	ft	. after	hours pum	ping gpm	
EST. YIELD. 12gpm. Well water was							
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well							
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Domestic Feedlot Oil field water supply Dewatering Other (Specify below)							
Industrial Domestic-lawn & garden Monitoring well							
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted							
mile Water well disinfected? Yes X No							
5 TYPE OF CASING USED: Steel PVC Other H.D. Tolyethylen C							
CASING JOINTS: Glued Clamped Welded Threaded Fusion Casing diameter 3/4 in. to 3.09 ft., Diameter in. to ft., Diameter ft., Diameter ft., Diameter ft., Wall thickness or gauge No. 160. PSI							
Casing height best land surface							
TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify)							
Brass Galvanized Steel None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE: None							
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut ☐ Other (specify)							
SCREEN-PERFORATED INTERVALS: From							
From							
GRAVEL PACK INTERVALS: From							
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☐ Bentonite ☐ Other							
Grout Intervals: From							
What is the nearest source of possible contamination: Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)							
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well							
☐ Watertight sewer lines ☐ Seep Direction from well		☐ Fertilizer : Distance	_	∐Oil well/ga ≊ll	s well	•••••	
	LOGIC LOG	FROM	TO			IGGING INTERVALS	
0 6 Soil+clay	(154-156 Shalp						
6 14 Sang	156-169 lime						
14 16 greysand 16 48 Sandy Shall	169-174 coa)	200	3	5-200'	harar alua	ged with	
16 48 tardy state 48 50 Coal	183-196 Shale	200	<u> </u>	High		Sentonite	
50 61 Shale	196-200 line			J			
50 61 Shale 61 74 grey sand 74 93 sandy Shale							
	 						
148 grey Sand 148 154 7:00e							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 7 constructed. Treconstructed, or 12 plugged							
under my jurisdiction and was completed on (mo/day/year) 8:-23: and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 599							
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.							
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for, each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.							
KSA 82a-1212							