WATER W	ELL RECO	ORD	Form WWC-5		Division of Wate	er Resources App. No).
1 LOCATION OF WATER WELL:			Fraction 14SE 14NE 14NE 14		Section Number	Township No.	Range Number
County: Douglas					29	T 13 S	R 20 XE □W
			if unknown, distance	Global Positionin	g System (GPS) in	formation:	
from nearest town or intersection: If at owner's address, check here .					Global Positioning System (GPS) information: Latitude: .33.53		
The second secon					Elevation: 835		
A WATER WELL OWNER,					Datum: WGS 8	84, □ NAD 83, □	NAD 27
2 WATER WELL OWNER: Tim Nouris RR#, Street Address, Box #: 1085 E . 1600 Rd					Collection Method:	CALL RANDO	Enth
City, State, ZIP Code					☐ GPS unit (Make/Model: Obtale. Cattle) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey		
0.11), 514		Low	rence, Ks.	•	Est. Accuracy:	<3 m, ☐ 3-5 m, ☐	5-15 m, $\square > 15$ m
3 LOCATE WELL							
WITH AN	WX"IN 4	DEPTH OF (COMPLETED WE	LL	ft (2)	A (*	2) #
SECTION BOX: Depth(s) Groundwater Encountered (1).55 ft. (2)							av/vr 2/6/13
N WELL'S STATIC WATER LEVEL 55							oinggpm
NW	NE @ E	ST. YIELD. 🧘	gpm. Well water was				ping gpm
w	E B	ore Hole Dian	neter 8 ? 1.8 in. to	E USED AS: Public water supply Geothermal Injection well			
							njection well
SWSE							omer (Specify below)
Was a chemical/bacteriological sample submitted to Department? Yes No							
S If yes, mo/day/yr sample was submitted							
Water well disinfected? ▼ Yes □ No							
5 TYPE OF CASING USED: Steel PVC Other							
CASING JOINTS: X Glued Clamped Welded Threaded							
CASING JOINTS: A Glued Clamped Welded Threaded Casing diameter 5.50 in to 51 ft., Diameter in to ft., Diameter in to ft. Casing height above land surface 13 in., Weight lbs./ft., Wall thickness or gauge No.							
Casing height above land surface. 10							
TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify)							
Brass Galvanized Steel None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole) Louvered shutter Key punched Wire wrapped Saw cut Other (specify)							
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)							
From ft., From ft. to ft.							
GRAVEL PACK INTERVALS: From 91 ft. to 40 ft., From ft. to ft.							
From ft. to ft., From ft. to ft.							
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other							
				ЭШ	u. w	, F10III	, 1t. tO1t.
What is the nearest source of possible contamination: Septic tank							
Sewer lines Cesspool Sewage lagoon Fuel storage							
11 5			oit Feedyard	Fertilizer st	from well . 2.0.0 .		
FROM T		LITHOLOG	FIC LOG	FROM			GGING INTERVALS
			city elays		He	3.3.(03221) 32.2.3	
0 8 8 28 28 33 33 50			. w/ un orial				
28 33	Efellow	ubun pan	dslone line	onte sta	rhed		
33 56	, Bray	Shallt	o Dandy oh	all	······		
56 40		spasston	<u>. </u>	i			
9D 91	June	stone					
040/42	and the same of th						
1,758,786				···			AWAMA
P. P. Park							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION; This water well was X constructed, \square reconstructed, or \square plugged							
under my jurisdiction and was completed on (mo/day/year) and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 732 This Water Well Record was completed on (mo/day/year), 2/13/13							
under the business name of a B. Environmental							
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.							
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include <u>fee</u> of \$5.00 for each <u>constructed</u> well. Visit us at http://www.kdheks.gov/waterwell/index.html .							
KSA 82a-1212							