

1 LOCATION OF WATER WELL: County: Johnson		Fraction NW 1/4 NW 1/4 SE 1/4	Section Number 24	Township Number 13 S	Range Number 21 E
Distance and direction from nearest town or city street address of well if located within city? 3 miles south of Clearview City, Kansas					
2 WATER WELL OWNER: Sunflower Army Ammunition Plant RR#, St. Address, Box # P.O. Box 549 35425 W. 103rd St City, State, ZIP Code DeSoto, Ks. 66018		Well No. MW-06 Board of Agriculture, Division of Water Resources Application Number: no data			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: no data ft. ELEVATION: no data ft. Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 11.1 ft. below land surface measured on mo/day/yr 8-19-95 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only X Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS 3/4" Blank casing diameter in. to ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface in., weight lbs./ft. Wall thickness or gauge No.		CASING JOINTS: Glued Clamped Welded Threaded. 7 PVC 10 Asbestos-cement 8 RMP (SR) 11 Other (specify) 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) unknown SCREEN-PERFORATED INTERVALS: From no data ft. to no data ft., From ft. to ft. GRAVEL PACK INTERVALS: From no data ft. to no data ft., From ft. to ft. From ft. to ft., From microfine cement ft. to ft.			
6 GROUT MATERIAL: 3.01 Neat cement 999 no data 2 Cement grout 3 Bentonite X Other microfine cement Grout Intervals: From ft. to ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Sewage pit 9 Feedyard 12 Fertilizer storage X Landfill 13 Insecticide storage 500 Direction from well? Northwest How many feet?		FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0.0 3.0 clay soil-tamped 3.0 unknown No well drilling or construction information available. The riser was 3/4" sch 80 PVC. Micro- fine cement was pumped under 60psi pressure until grout was returned at the surface and well would accept no more grout. The well was then excav- ated to 3', the casing cut off and the hole backfilled with clay soil and tamped. The total grout take was 70.0 gallons. CF: KDHE, Bureau of Water SFAAP USACE-MRK-EP-GG Calculated grout volume = 57.0 gal Actual grout take = 70.0 gal			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or X plugged under my jurisdiction and was completed on (mo/day/year) 8-21-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. U.S. Army Corps of Engineers - RCD This Water Well Record was completed on (mo/day/yr) 9-29-95 under the business name of by (signature) [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					